

											
MODEL	DCP-L5500DN	DCP-L6600DW	MFC-L5700DN	MFC-L5750DW	MFC-L6800DW	MFC-L6900DW	DCP-L8400CDN	DCP-L8450CDW	MFC-L8650CDW	MFC-L8850CDW	MFC-L9550CDWT
Fax/imprimare/copiere/scanare A4	- / da / da / da	- / da / da / da	da / da / da / da	da / da / da / da	da / da / da / da	da / da / da / da	- / da / da / da	- / da / da / da	da / da / da / da	da / da / da / da	da / da / da / da
Viteză imprimare mono/color	40 ppm/-	46 ppm /-	40 ppm/-	40 ppm/-	46 ppm /-	50 ppm /-	28/28 ppm	30/30 ppm	30/30 ppm	30/30 ppm	30/30 ppm
Timp ieșire prima pagină	7,2 sec	7,5 sec	7,2 sec	7,2 sec	7,5 sec	7,5 sec	< 15 sec,	< 15 sec,	< 15 sec,	< 15 sec,	< 15 sec,
Viteză copiere mono/color	40 cpm/-	46 cpm /-	40 cpm/-	40 cpm/-	46 cpm /-	50 cpm /-	28/28 ppm	30/30 ppm	28/28 ppm	30/30 ppm	30/30 ppm
Rețea	cablată	cablată/wireless	cablată	cablată/wireless	cablată/wireless	cablată/wireless	cablată	cablată/wireless	cablată/wireless	cablată/wireless	cablată/wireless
Imprimare/copiere/scanare/fax duplex	da / - / - / -	da / da / da / -	da / da / - / -	da / da / da / da	da / da / da / da	da / da / da / da	da / - / - / -	da / da / da / -	da / da / da / da	da / da / da / da	da / da / da / da
Rezoluție imprimare	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi	2400 x 600 dpi	2400 x 600 dpi	2400 x 600 dpi	2400 x 600 dpi	2400 x 600 dpi
Rezoluție copiere	1200 x 600 dpi	1200 x 600 dpi	1200 x 600 dpi	1200 x 600 dpi	1200 x 600 dpi	1200 x 600 dpi	1200 x 600 dpi	1200 x 600 dpi	1200 x 600 dpi	1200 x 600 dpi	1200 x 600 dpi
Imprimare USB Host/PictBridge	da	da	da	da	da	da	da/-	da/-	da/-	da/-	da/-
ADF (Alimentator automat de documente)	40 coli	80 coli	50 coli	50 coli	80 coli	80 coli	35 coli	50 coli	35 coli	50 coli	50 coli
Capacitate alimentare	250 coli	520 coli	250 coli	250 coli	520 coli	520 coli	250 coli	250 coli	250 coli	250 coli	750 coli
Tavă universală	50 coli	50 coli	50 coli	50 coli	50 coli	50 coli	50 coli	50 coli	50 coli	50 coli	50 coli
Tavă ieșire față în sus/jos	1/150 coli	10/250 coli	1/150 coli	1/150 coli	10/250 coli	10/250 coli	-/150 coli	1/150 coli	1/150 coli	1/150 coli	1/150 coli
Capacitate alimentare opțională	până la 1040 coli	până la 2650 coli	până la 1040 coli	până la 1040 coli	până la 2650 coli	până la 2650 coli	1 x 500 coli	1 x 500 coli	1 x 500 coli	1 x 500 coli	1 x 500 coli
Capacitate memorie	256 MB	512 MB	256 MB	256 MB	512 MB	1GB	256 MB (256 MB)	256 MB (256 MB)	128 MB (256 MB)	256 MB (256 MB)	256 MB (256 MB)
Interfață	Hi-Speed USB 2,0, Ethernet-10/100 Base-TX	Hi-Speed USB 2,0, Ethernet-10/100/1000 Base-TX Wifi- 802,11b/g/n (Wi-Fi Direct), NFC	Hi-Speed USB 2,0, Ethernet-10/100 Base-TX	Hi-Speed USB 2,0, Ethernet-10/100/1000 Base-TX Wifi- 802,11b/g/n (Wi-Fi Direct)	Hi-Speed USB 2,0, Ethernet-10/100/1000 Base-TX Wifi- 802,11b/g/n (Wi-Fi Direct), NFC	Hi-Speed USB 2,0, Ethernet-10/100/1000 Base-TX Wifi- 802,11b/g/n (Wi-Fi Direct), NFC	Hi-Speed USB 2,0; Ethernet-10/100 Base-TX	Hi-Speed USB 2,0; Ethernet-10/100 Base-TX IEEE 802,11b/g/n (mod infrastructură/Ad-hoc) IEEE 802,11g (Wi-Fi Direct)	Hi-Speed USB 2,0; Ethernet-10/100 Base-TX IEEE 802,11b/g/n (mod infrastructură/Ad-hoc) IEEE 802,11g (Wi-Fi Direct)	Hi-Speed USB 2,0; Ethernet-10/100 Base-TX, IEEE 802,11b/g/n (mod infrastructură/Ad-hoc) IEEE 802,11g (Wi-Fi Direct)	Hi-Speed USB 2,0; Ethernet-10/100 Base-TX, IEEE 802,11b/g/n (mod infrastructură/Ad-hoc) IEEE 802,11g (Wi-Fi Direct) NFC
Emulare	PCL6, BR-Script3 (limbaj emulare PostScript®3TM), IBM Proprinter XL, Epson FX-850, PDFversiune1,7, XPS versiune 1,0	PCL6, BR-Script3 (limbaj emulare PostScript®3TM), IBM Proprinter XL, Epson FX-850, PDF versiune 1,7, XPS versiune 1,0	PCL6, BR-Script3 (PostScript®3TM Language Emulation), IBM Proprinter XL, Epson FX-850, PDF versiune 1,7, XPS versiune 1,0	PCL6, BR-Script3 (limbaj emulare PostScript®3TM), IBM Proprinter XL, Epson FX-850, PDF versiune 1,7, XPS versiune 1,0	PCL6, BR-Script3 (limbaj emulare PostScript®3TM), IBM Proprinter XL, Epson FX-850, PDF versiune 1,7, XPS versiune 1,0	PCL6, BR-Script3 (limbaj emulare PostScript®3TM), IBM Proprinter XL, Epson FX-850, PDF versiune 1,7, XPS versiune 1,0	PCL®6, BR-Script3	PCL®6, BR-Script3	PCL®6, BR-Script 3	PCL®6, BR-Script3	PCL®6, BR-Script3
Ecran	Ecran tactil color 9,3cm	Ecran tactil color TFT 12,3 cm	Ecran tactil color 9,3cm	Ecran tactil color TFT 12,3 cm	Ecran tactil color TFT 12,3 cm	Ecran tactil color TFT 12,3 cm	LCD color TFT 9,3 cm	LCD color TFT 12,3 cm	LCD color TFT 9,3 cm	LCD color TFT 12,3 cm	LCD color TFT 12,3 cm
Suport driver de imprimantă	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux
Viteză modem	-	-	33,6 bps	33,6 bps	33,6 bps	33,6 bps	-	-	33,6 kbps	33,6 kbps	33,6 kbps
Rezoluție scanare (îmbunătățită)	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 2400 dpi	1200 x 2400 dpi	1200 x 2400 dpi	1200 x 2400 dpi	1200 x 2400 dpi
Altele	Certificare Energy Star, Blauer Engel, Nordic Swan, GS, BSI	Certificare Energy Star, Blauer Engel, Nordic Swan, GS, BSI	Certificare Energy Star, Blauer Engel, Nordic Swan, GS, BSI	Certificare Energy Star, Blauer Engel, Nordic Swan, GS, BSI	Certificare Energy Star, Blauer Engel, Nordic Swan, GS, BSI	Certificare Energy Star, Blauer Engel, Nordic Swan, GS, BSI	Certificare Energy Star, Blauer Engel, Google Cloud Print, Air Print, BSI	Certificare Energy Star, Blauer Engel, Google Cloud Print, Air Print, BSI	Certificare Energy Star, Blauer Engel, Google Cloud Print, Air Print, BSI	Certificare Energy Star, Blauer Engel, Google Cloud Print, Air Print, BSI	Certificare Energy Star, Blauer Engel, Google Cloud Print, Air Print, BSI
Dimensiuni (L x l x î) & greutate (kg) fără carton	435 x 427 x 486 mm 16,4 kg	495 x 427 x 518 mm 18,5 kg	435 x 427 x 486 mm 16,5 kg	435 x 427 x 486 mm 16,5 kg	495 x 427 x 518 mm 18,9 kg	495 x 427 x 518 mm 19 kg	410 x 503 x 492 mm 29 kg	490 x 526 x 530 mm 30,2 kg	410 x 503 x 492 mm 30,4 kg	490 x 526 x 530 mm 31 kg	490 x 535 x 662 mm 37,4 kg