



Model	HL-L5000D	HL-L5100DN	HL-L5200DW	HL-L6300DW	HL-L6400DW	HL-L8250CDN	HL-L8350CDW	HL-L9200CDWT
Viteză de imprimare A4 mono/color	40 ppm	40 ppm	40 ppm	46 ppm	50 ppm	28/28 ppm	30/30 ppm	30/30 ppm
Timp ieșire prima pagină	7,2 sec	7,2 sec	7,2 sec	7,5 sec	7,5 sec	< 15 sec,	<15 sec,	<15 sec,
Rețea	-	cablată	cablată/wireless	cablată/wireless	cablată/wireless	cablată	cablată/wireless	cablată/wireless
Imprimare duplex	automată	automată	automată	automată	automată	automată	automată	automată
Rezoluție imprimare	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi	2400 x 600 dpi	2400 x 600 dpi	2400 x 600 dpi
Imprimare USB Host/PictBridge	-	-	-	-	-	da / -	da / -	da / -
Capacitate alimentare	250 coli	250 coli	250 coli	520 coli	520 coli	250 coli	250 coli	750 coli
Tavă universală	50 coli	50 coli	50 coli	50 coli	50 coli	50 coli	50 coli	50 coli
Capacitate alimentare opțională	până la 1040 coli	până la 1040 coli	până la 1040 coli	până la 2650 coli	până la 2650 coli	1 x 500 coli	1 x 500 coli	1 x 500 coli
Tavă ieșire față în sus/jos	1/150 coli	1/150 coli	1/150 coli	10/250 coli	10/250 coli	1/150 coli	1/150 coli	1/150 coli
Capacitate memorie	128 MB	256 MB	256 MB	256 MB	512 MB	128 MB (256MB)	128 MB (256 MB)	128 MB (256 MB)
Interfață	Hi-Speed USB 2,0 IEEE 1284 Paralel	Hi-Speed USB 2,0, Ethernet-10/100 Base-TX	Hi-Speed USB 2,0, Ethernet-10/100 Base-TX Wifi- 802,11b/g/n (Wi-Fi Direct)	Hi-Speed USB 2,0, Ethernet-10/100 Base-TX Wifi- 802,11b/g/n (Wi-Fi Direct), NFC	Hi-Speed USB 2,0, Ethernet-10/100 Base-TX Wifi- 802,11b/g/n (Wi-Fi Direct), NFC	Hi-Speed USB 2,0; Ethernet-10/100 Base-TX	Hi-Speed USB 2,0; Ethernet-10/100 Base -TX, IEEE 802,11b/g/n (Mod infrastructură/Ad-hoc) IEEE 802,11g (Wi-Fi Direct)	Hi-Speed USB 2,0; Ethernet-10/100 Base -TX, IEEE 802,11b/g/n (Mod infrastructură/Ad-hoc) IEEE 802,11g (Wi-Fi Direct)
Emulare	PCL6, BR-Script3 (limbaj emulare PostScript®3TM), IBM Proprinter XL, Epson FX-850, PDF versiune 1,7, XPS versiune 1,0	PCL6, BR-Script3 (limbaj emulare PostScript®3TM), IBM Proprinter XL, Epson FX-850, PDF versiune 1,7, XPS versiune 1,0	PCL6, BR-Script3 (limbaj emulare PostScript®3TM), IBM Proprinter XL, Epson FX-850, PDF versiune 1,7, XPS versiune 1,0	PCL6, BR-Script3 (limbaj emulare PostScript®3TM), IBM Proprinter XL, Epson FX-850, PDF versiune 1,7, XPS versiune 1,0	PCL6, BR-Script3 (limbaj emulare PostScript®3TM Language Emulation), IBM Proprinter XL, Epson FX-850, PDF versiune 1,7, XPS versiune 1,0	PCL®6, BR-Script 3	PCL®6, BR-Script 3	PCL®6, BR-Script 3
Ecran	Ecran LCD 1 linie, 16 caractere iluminat	Ecran LCD 1 linie, 16 caractere iluminat	Ecran LCD 1 linie, 16 caractere iluminat	Ecran tactil color 4,5 cm	Ecran tactil color 4,5 cm	LCD: 2-linii, 16-caractere	LCD: 2-linii, 16-caractere	4,5 cm TFT
Suport driver de imprimantă	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux	Win/Mac/Linux
Altele	Certificare Energy Star, Blauer Engel, Nordic Swan, GS	Certificare Energy Star, Blauer Engel, Nordic Swan, GS	Certificare Energy Star, Blauer Engel, Nordic Swan, GS	Certificare Energy Star, Blauer Engel, Nordic Swan, GS, BSI	Certificare Energy Star, Blauer Engel, Nordic Swan, GS, BSI	Certificare Energy Star, Blauer Engel, Google Cloud Print, Air Print	Certificare Energy Star, Blauer Engel, Google Cloud Print, Air Print	Certificare Energy Star, Blauer Engel, Google Cloud Print, Air Print, BSI
Dimensiuni (L x l x İ), greutate kg fără carton	373 x 388 x 255 mm 10,7 kg	373 x 388 x 255 mm 10,7 kg	373 x 388 x 255 mm 10,7 kg	400 x 396 x 288 mm 13,2 kg	400 x 396 x 288 mm 13,4 kg	410 x 486 x 313 mm 21,9 kg	410 x 486 x 313 mm 21,9 kg	410 x 495 x 445 mm 28,3 kg