brother®

MFC-8440

Optional Network Interfa

Telephone

Technical Specification

General			Laser Fax		
Engine LCD Display Memory Capacity Automatic Document Feeder Paper handling size Paper Capacity Simultaneous Operation	Standard paper casette Optional paper casette Output paper capacity	Laser 5 lines x 22 characters 32MB standard / 160MB maximum up to 50 sheets 4/LTR1/L0.Efs/A/56/A6/EXE up to 250 sheets (UF.5000) up to 150 sheets (UF.5000) up to 150 sheets (UF.6000) (Phint/Scan) (Phint/Fax)	Dual Access Modern Data Compression Automatic redial One-touch dials Speed dials Fax / Tel switch Distinctive ring detection Super fine		Scan a fax for transmission whilst receivi 33.bitps Super G3 Approx 2 seconds transmission MH / MR / MMR / JBIG Automatic redial if the recipient fax is busy 40 locations for one-fouch auto dailing of pre-store Automatic recognition of fax and telephon Yes - UK & Demmark only Enables quality transmission and reception of
		(rinteopy) (rinteocar) (rinterasy	Grey scale		64 shades of grey
Laser Copier			Delayed timer Memory Transmission		Yes - up to 50 Up to 500 pages (ITU-T Test Chart No 1)
Speed Resolution Multi copy		Up to 20cpm Max. 1200 x 600dpi Produces up to 99 copies of each original	Out of paper reception Broadcasting locations		Up to 500 pages (ITU-T Test Chart No 1) send the same fax message to up to 390 50 manual locations
Stack & Sort		Stacks or sorts output copies as desired	Batch transmission		Stores documents for the same location in transmission in a single call
Enlargement / reduction ratio		25% - 400% in 1% increments	Auto reduction		Automatically reduces a received fax to fit
N in 1 Poster Printing		Compress 2 or 4 pages on to a single sheet Enlarge image to poster size	Error correction mode		Where machines share ECM, it resends to where an error has occured
Laser Printer			Fax forwarding		Sends a fax received in memory to anoth number
Speed Resolution Standard print language	Simplex	Up to 20ppm Max: 2400 x 600dpi Windows @GDI	Remote access Fax retrieval PBX		Allows the user to remotely access their r touch tone phone Allows the user to retrieve fax messages us Enables compatability with PBX's that use
Emulation Secure Print		PCL6 & BR-Script 3 (Postscript® 3 Language Emulation) Prevents unauthorised printing of protected documents	Weights and Dimension	ns	
Colour Scanner			Dimensions / Weight	With Carton Without Carton	567(w) x 628(d) x 575(h) mm / 21.8kg 532(w) x 444(d) x 469(h) mm / 16.6kg
Resolution	Optical Interpolated	Max. 600 x 2400dpi Max. 9600 x 9600dpi	Consumables & Option	nal Accessories	
Grey Scale Colour Depth 'Scan' key	Interpolated	max seoux seouup 256 shades of grey 48 bit internal / 24 bit external Scan to e-mail/OCR/Image/File*	Toner Drum Lower Paper Tray	Standard High Yield	TN-3030 - 3,500 pages with 5% covera TN-3060 - 6,700 pages with 5% covera DR-3000 - 20,000 pages @ 1 page pe LT-5000 - additional 250 sheets
Interface			Network Print/Fax Server		NC-9100h - with 5 user license (Option: NL-5 - optional 5 user license [†]
Parallel USB		IEEE1284 Parallel Cable Port HI-Speed USB2.0	Other Information		
Network 10/100Base-TX Etherner		Optional - NC-9100h	Power Consumption	Operating Sleep / Standy / Peak	450W or less (Copying) 14W / 85W / 1090W or less
*Windows® only				CPU Sleep	6W or less

	Scan a fax for transmission whilst receiving or sending a fax
	33.6kbps Super G3
	Approx 2 seconds transmission
	MH/MR/MMR/JBIG
	Automatic redial if the recipient fax is busy
	40 locations for one-touch auto dialling of pre stored numbers
	300 locations for auto dialling of pre-stored numbers
	Automatic recognition of fax and telephone reception
	Yes - UK & Denmark only
	Enables quality transmission and reception of very small print or line drawings
	64 shades of grey
	Yes - up to 50
	Up to 500 pages (ITU-T Test Chart No 1)
	Up to 500 pages (ITU-T Test Chart No 1)
	send the same fax message to up to 390 pre-programmed / 50 manual locations
	Stores documents for the same location in the machines memory for transmission in a single call
	Automatically reduces a received fax to fit on to a singles sheet of A4
	Where machines share ECM, it resends the page(s) of a document
	where an error has occured
	Sends a fax received in memory to another pre-programmed fax number
	Allows the user to remotely access their machine by using another touch tone phone
	Allows the user to retrieve fax messages using another touch tone phone
	Enables compatability with PBX's that use Time Break Recall
	567(w) x 628(d) x 575(h) mm / 21.8kg 532(w) x 444(d) x 469(h) mm / 16.6kg
ies	
	TN-3030 - 3,500 pages with 5% coverage
	TN-3060 - 6,700 pages with 5% coverage

⁺ Up to a maximum of 25 users	
--	--

MFC-8440	Scanner Resolution	TWAIN/WIA Driver	Scan to Image	Scan to E-mail	Scan to OCR	Scan to File	Scan to E-mail Server	Brother PC-FAX Send	PC-FAX Receive	Printer Driver	Brother Control Centre	Remote Setup	NewSoft Presto!® Page Manager®	ScanSoft® PaperPort®
Microsoft Windows® 98(SE)/Me/2000 Professional NT® 4.0 Workstation XP	9600x9600 9600x9600 1200x1200*	TWAIN TWAIN * WIA	√* √ √*	/* / /*	/* / /*	/* / /*	/* /* /*	/* /* /*	111	√* √* √*]*]]*	1.5.5		√* √ √*
Macintosh® OS 8.6 OS 9.x OS 10.1 OS 10.2.1-10.3 or greater	9600x9600 9600x9600 - 9600x9600	TWAIN TWAIN - TWAIN					/* /* /* /*]*]*]*]*		√* √* √* √*		1 1	1 1 1	

MINIMUM	SYSTEM REQUIRE	MENTS	AVAILABLE HARD DISK SPACE					
COMPUTING SYSTEM	OPERATING SYSTEM VERSION	PROCESSOR SPEED	MINIMUM RAM	RECOMMENDED RAM	for Drivers and ScanSoft® Software	for Drivers and NewSoft Presto!® Page Manager® Software		
*SWODNW	98/98SE Me NT® 4.0 Workstation 2000 Professional XP	Pentium 75MHz Pentium 150MHz Pentium 75MHz Pentium 133MHz Pentium 233MHz	32MB 32MB 32MB 64MB 128MB	32MB 64MB 64MB 128MB 256MB	180MB 180MB 180MB 180MB 260MB			
MAC	OS 8.6 - OS 9.2 OS 10.1 OS 10.2.1 - 10.3 or greater	All base models meet minimum requirements	32MB 128MB 128MB	64MB 160MB 160MB		250MB 250MB 250MB		

*This feature is also available when optional NC-9100h Print/Fax Server installed. **Brother Scanner Utility enables to enhance up to 9600 x 9600dpi





Brother International Europe Ltd

Brother House, 1 Tame Street, Audenshaw, Manchester M34 5JE Tel: + 44 (0) 161-330 6531 Fax: + 44 (0) 161-330 5520 Web-site: www.brother.com

All specifications correct at time of printing. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks or trademarks of their respective companies







Four essential functions, each individually impressive.

Optional Network Connectivity

The MFC-8440 offers an optional NC-9100h Print/Fax Server that enhances your machine into a workgroup MFC. This ensures effortless implementation into the majority of networks and supporting industry standard speed (10/100BaseTX) and protocols (TCP/IP, IPX/SPX, AppleTalk).

For the User

- Network Printing • The NC-9100h offers Network printing functionality across
- the most popular protocols and platforms including Microsoft Windows®, Macintosh®, Novell, Unix and Linux operating systems

Network scanning

- Scansoft[®] PaperPort[®] with 5 user licence
- Brother control centre for effortless Network Scanning
- Scan to key functionality
- Further optional 5 user licence agreements to extend workgroup capability up to a maximum 25 users

For the IT Administrator Network Management

running low or an error occurs.

environments so Brother provides a number of

tools to help you proactively manage your

In addition Brother provides its BRAdmin

connected printers, MFC's and DCP's.

For a full list of specifications for the

NC-9100h Print Server please go to

http://solutions.brother.com

Professional Software for administering LAN

Brother supplies are designed to allow Manageability is essential in today's busy network easy replacement

Benefits of this to you are: The toner and drum are compatible

network-connected printers, MFC's and DCP's. with the complete range of products An Embedded Web Server provides a platform in this generation, which means that that can be accessed from any web browser to you only need to order and stock one manage vour device. E-mail notification can alert range of consumables. administrators or users when a consumable is Separate toner and drums reduce wastage and overall costs.

Brother Supplies

- High yield and standard yield toners
- to suit your usage and budget requirements. The supplies:
- TN-3030 Standard yield toner TN-3060 - High yield toner DR-3000 – Printing drum



al lower trav (LT5000



${\sf MFC}\mbox{-}8440$ With / without lower tray

- Laser Printer
- Laser Fax
- Laser Copier Colour Scanner
- Optional Network Interface

Laser Printing

With print speeds of up to 20 pages per minute and a resolution of up to 2400 x 600 dots per inch, you can be certain of both the quality and performance of this machine. Coping with office print demands is no problem, thanks to a generous 32MB of standard memory, which can be expanded to up to 160MB. Both PCL®6 and BR-Script 3 (PostScript® 3 language emulations) are installed, and confidentiality is assured with the Secure Print feature. Furthermore, with the choice of parallel, Hi-Speed USB 2.0 and optional network, connecting to the most popular PC operating systems presents no problem.



For easy faxing of multi-page documents

Laser Faxing

The MFC-8440 offers you the versatility of faxing bound documents using the flatbed or multi-page documents via the 50 sheet Automatic Document Feeder. A modem speed of 33.6kbps means that faxes can be sent in as little as 2 seconds per page. For added convenience, 40 one-touch numbers can be dialled quickly and easily, as can a further 300 speed dial numbers. What's more, the combined 'out of paper' and 'fax transmission' memory facility stores up to 500 pages[†], whilst memory security ensures that your confidential documents stay that way. [†]ITU-T Test Chart No.⁺

Software

Brother supplies industry standard software to enhance the key functions of your

- machine Scansoft[®] Paperport[®]* Turns piles of paper and photos into organised digital files that you can guickly find use and share.
- OCR software* Easily turns printed pages into editable
- Brother PC-Fax software* Send and receive faxes directly from your PC.
- Remote set up facility* Configure the settings of your
- NewSoft Presto!® Page Manager® for Macintosh® including OCR* Document management software for Macintosh users including OCR
- *Please see driver table for details on your operating



Colour Flatbed scanning Send images directly to OCR, E-mail, Image or File

Colour Scanner

This MFC offers an uncompromised resolution quality of up to 9600 x 9600 dpi. Scans can be generated through the Automatic Document Feeder or flatbed and sent directly to OCR, E-mail, Image or File. Besides these four main functions, this all-inone machine offers the convenience of simultaneous operation. This allows you to use the scan function while a print-out is being generated or print a document whilst sending a fax.

Backlit keys for Fax, Copy and Scan enable instant access to each function.

Laser Copying

The availability of both a flatbed and a 50 sheet Automatic Document Feeder provides flexibility when copying. You can produce up to 99 copies at one time and stack and sort functions present your documents without the need for rearranging. For added versatility. 2 in 1 and 4 in 1 scale functions. as well as poster printing, are available.







MFC-**8440** multifunction machine