# MFC-9140CDN





# Colour LED Multi-Function Centre® with Networking Capability

The MFC-9140CDN is a high speed all-in-one, offering network connectivity and 2-sided printing to suit your busy office.

- Print / Copy / Scan / Fax
- Fast Printing Up to 22ppm colour and monochrome printing
- Save Money Automatic 2-sided (duplex) Printing
- Convenience Print without PC using mobile print
- Easy Sharing Connect with multiple users via wired/wireless network
- Reduce Running Costs- Choice of high-yield colour toners for heavy print volume

# MFC-9140CDN

For increased productivity, the MFC-9140CDN offers amazingly fast and efficient colour and monochrome print speeds of up to 22 pages per minute and multi-functions - print, scan, copy and fax.

With automatic 2-sided printing, you can print on both sides and save on costs. Share your printer easily with other users by connecting it via the built-in network. With the mobile print capability, you can print your documents from your mobile without the use of a PC. Navigate easily with the intuitive 9.3cm colour Touch Screen display and improve your productivity in the office.

Brother's high-yield toner cartridges will enable you to enjoy a lower cost per page for large print volumes. For greater efficiency and more cost savings, Brother is the perfect choice.

#### **General**

Technology Memory
Local Interface
Wired Network Interface Display Mobile Connectivity

Electrophotographic LED Printer 192MR 132/wib HI-Speed USB 2.0 Ethernet (10Base-T/100Base-TX) 9.3cm TFT colour touchscreen Brother iPrint&Scan app, AirPrint & Google Cloud Print™

Web Connect Print from and scan to Box, DropBox, Evernote®, Facebook, Flickr®,

Google Drive™, PicasaTM & SkyDrive®





# **Supported Operating Systems**

Windows 8° (32 & 64 bit editions), Windows 7° (32 & 64 bit editions), Windows

Windows Vista® (32 & 64 bit editions)

Windows® XP Professional (32 & 64 bit editions), Windows® XP Home

Edition.

Windows® Server 2012, Windows® Server 2008 R2, Windows® Server 2008 (32 & 64 bit editions), Windows® Server 2003 (32 & 64 bit editions), Windows® Server supports printing only Mac OS X 10.6.8, 10.7.x, 10.8.x CUPS, LPD/LPRng (x86/x64 environment)

**Automatic 2-Sided Colour Printer** 

Print Speed (A4) 2-Sided Print Speed (A4) Resolution Print Languages FPOT (First Print Out Time) Warm Up Time Up to 22ppm (pages per minute) colour & mono Up to 7ipm (images per minute) colour & mono 2,400dpi (2,400 x 600dpi2), 600 x 600dpi PCL6, BR-Script3 (PostScript\*3TM Language Emulation) Less than 16 seconds colour & mono from ready mode Less than 24 seconds from sleep mode

**Colour Fax** 

Modem 33 6kbps Super G3 Speed Dials

200 locations for pre-stored numbers

Page Memory Up to 500 pages (ITU-T Test Chart, Standard Resolution, JBIG) Other Functions Fax forwarding, remote access, fax retrieval, dual access, I-Fax3, PC-Fax send, PC-Fax receive4, auto reduction, group dials,

**Colour Copier** 

Speed (A4) Up to 22cpm (copies per minute) colour & mono Resolution 600 x 600dpi

Makes up to 99 copies of each page (stacks or sorts) Multi copy

Enlargement / Reduction Ratio Reduce & enlarge documents from 25% to 400% using 1% increments

**Colour Scanner** 

Resolution Up to 1,200 x 2,400dpi (from flatbed), 1,200 x 600dpi (from ADF),

19,200 x 19,200dpi (interpolated)

Grev Scale 256 shades of grev

Colour Depth 4 8bit internal / 24bit external colour scanner Scan to email, OCR, image, file & searchable PDF Pull Scan Functions

(requires bundled software) Push Scan Functions Scan to network folder4. FTP & email server

TWAIN, WIA, ICA, SANE Drivers

## **Paper Handling**

Paper Output Media Type

Media size

50 sheet standard paper tray Paper Input 1 sheet manual feed slot

35 sheet automatic document feeder (ADF) 100 sheets face down, 1 sheet face up (straight paper path)

Standard Tray - Plain & recycled paper (60 - 105g/m²)

Manual Feed Slot - Plain, recycled, glossy & bond paper (60 - 163g/m²) ADF - Plain & recycled paper (64 - 90g/m²)

Standard Tray - Á4, Letter, B5 (JIS), A5, A5 (Long Edge), A6, Executive, Legal, Folio (A4 only supported in automatic 2-sided print mode)

Manual Feed Slot - Width: 76.2 to 215.9mm x Length: 116 to 355.6mm ADF - Width: 147.3mm to 215.9mm x Length 147.3mm to 355.6mm Yes, from manual feed slot (accuracy & reliability will depend on the quality & Envelope & Label Printing

type of media used)

### **Windows Printer Driver Functions**

Reduce up to 2, 4, 9, 16 or 25 A4 pages into just one A4 page N-up Printing

(also supported by Mac)

Poster Printing Enlarge 1 A4 page into a poster using 4, 9, 16 or 25 A4 pages Watermark Printing Add predefined text to your documents as a watermark Add identification to your printed documents ID Printing

Booklet Printing Print documents in A5 booklet format Skip Blank Page Ignores any blank pages in your documents Print Text in Black Converts all text in your documents to black when printed

**Supplies** 

Macintosh

Inbox Toners Standard Toners

High Yield Colour Toners

Waste Toner Box

1,000 pages¹
TN-251BK - 2,500 pages¹
TN-251CMY - 1,400 pages¹
TN-255C/M/Y - 2,200 pages¹
TN-255CL - 15,000 A4 pages
BU-220CL - Up to 50,000 pages
WT-220CL - Up to 50,000 pages



Without Carton 410(W) x 483(D) x 410(H) mm 18.5kg

**Environment** 

375W active, 70W ready, 7.5W sleep, 0.05W deep sleep Power Consumption

Sound Pressure 53dBA active, 33dBA ready Sound Power 6.42B active, 4.44B ready

Power Save Consume less energy when not in use Toner Save

Reduces toner usage

**Duty Cycle** 

Recommended Monthly Print Volume
Maximum Monthly Volume<sup>5</sup>

300 to 1,500 pages Up to 30,000 pages



Maximum number of printed pages per month and can be used to compare designed durability between like for like Brother products. For maximum printer life, it is best to choose a printer with a duty cycle that far exceeds your print requirements Windows only Maximum number of printed pages per month and can be used to compare designed durability between like for like Brother products. For maximum printer life, it is best to choose a printer with a duty cycle that far exceeds your print requirements







Approx. declared yield value in accordance with ISO/IEC19798 2Vertical x horizontal