Xerox[®] Phaser[®] 6510 Colour Printer





System Specification	Phaser 6510N	Phaser 6510DN	Phaser 6510DNI	
One-Sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 30 ppm Colour and Black and White Up to 28 ppm Colour and Black and White Up to 24 ppm Colour and Black and White			
Two-Sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 18 ppm Colour and Black and White Up to 19 ppm Colour and Black and White Up to 17 ppm Colour and Black and White			
Monthly Duty Cycle ¹	Up to 50,000 pages / month			
Recommended Average Monthly Print Volume ²	Up to 3,000 pages			
Processor	733 MHz			
Memory	1 GB			
Connectivity	10/100/1000Base-T Ethernet USB 3.0		10/100/1000Base-T Ethernet USB 3.0 Wi-Fi 802.11n Wi-Fi Direct®	
Paper Handling	Phaser 6510N	Phaser 6510DN	Phaser 6510DNI	
Bypass Tray				
Capacity ³	50 sheets			
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm			
Weights	16 lb. bond to 58 lb. cover / 60 to 220 gsm	16 lb. bond to 58 lb. cover / 60 to 220 gsm		
Media Types	Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled			
Tray 1				
Capacity ³	250 sheets			
Sizes	Custom Sizes 3 x 5.8 in. to 8.5 x 14 in. / 76 x 147 mm to 216 x 356 mm			
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm			
Media Types	Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled			
	Recycled			
Optional Tray 2	Recycled			

Optional Tray 2			
Sizes	Custom Sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x	: 191 mm to 216 x 356 mm	
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm		
Media Types	Bond Plain Card Stock Custom Glossy Card Stock Hole punched Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled		
Total Capacity			
Device Standard Capacity ³	300 sheets		
Device Total Capacity ³	850 sheets		
Paper Output			
Output Capacity ³	150 sheets		
Automatic 2-Sided	Optional	Standard	
Device Specification	Phaser 6510N	Phaser 6510DN	Phaser 6510DNI
Electrical Requirements			
North America	Voltage: 120 VAC +/- 10 % Frequency: 60 Hz +/- 3 Hz, 12A		
Europe	Voltage: 220-240 VAC +/- 10% Frequency: 50 Hz +/- 3 Hz, 6A		
Power Consumption			
Operation ³	120V: Maximum 380 watts 220V: Maximum 350 watts		
Standby Mode ⁴	120V: Maximum 41 watts 220V: Maximum 44 watts		
Power Off Mode ⁴	120V: Maximum 0.2 watts 220V: Maximum 0.3 watts		
Sleep Mode ⁴	120V: Maximum 0.9 watts 220V: Maximum 1.0 watts		
Warm-up (from Sleep Mode)	As fast as 26 seconds		
Operating Environment			
Required Temperature Range Storage Operating	-4°F to 104°F / -20°C to 40°C 41°F to 90°F / 5°C to 32°C		
Required Reletive Humidity	15% to 85%		
Sound Power Levels Operating Standby	6.76 B or less 4.00 B or less		
Sound Pressure Levels Operating Standby	51.9 dB(A) or less 24.9 dB(A) or less		
Dimensions and Weight (unpackaged)			
Phaser 6510N, and DN	Width: 16.5 in. / 420 mm Depth: 19 in. / 483 mm Height: 13.7 in. / 347 mm Weight: 52.5 lb. / 23.8 kg		
Phαser 6510 DNI	Width: 16.5 in. / 420 mm Depth: 19.6 in. / 499 mm Height: 13.7 in. / 347 mm Weight: 52.5 lb. / 23.8 kg		

Dimensions and Weight (unpackaged)			
550-sheet Paper Tray	Width: 16.5 in. / 420 mm Depth: 18.3 in. / 465 mm Height: 5.9 in. / 150 mm Weight: 14.8 lb. / 6.7 kg		
Dimensions and Weight (packaged)			
Phaser 6510N, DN, and DNI	Width: 14.3 in. / 634 mm Depth: 22.8 in. / 580 mm Height: 19.9 in. / 505 mm Weight: 64.4 lb. / 29.2 kg		
550-sheet Paper Tray	Width: 21.1 in. / 535 mm Depth: 23 in. / 584 mm Height: 9.8 in. / 248 mm Weight: 18.7 lb. / 8.5 kg		
System Certification/Regulatory Compliance	ce control		
Certifications	FCC Part 15 Class A FCC Part 68 CE Mark applicable to Directives 2006. UL 60950-1/CSA 60950-1-07, 2nd Edit NOM GS Mark EAC Citrix Certified Cerner (undergoing evaluation) Apple® AirPrint® certification Google Cloud Print Certification Mopria® certified Wi-Fi Alliance Certified Blue Angel MEDITECH ENERGY STAR® ECOLOGO® EPEAT (United States) To view the latest list of certifications,		ı.
Print	Phaser 6510N	Phaser 6510DN	Phaser 6510DNI
First-Page-Out Time	As fast as 12 seconds Colour and Black	and White	
Resolution	Up to 1200 x 2400 dpi		
Page Description Languages	Adobe® PostScript® 3 [™] PCL® 5e, 6 PDF TIFF		
Maximum Print Area	4 mm from all edges		
Print Features	Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Secure Print Watermarks		
Print from USB	Allows walk-up printing from Type A U: Supports direct printing from compute Supported file formats: PDF, JPEG, TIFI	r via Type B USB port	

Print	Phaser 6510N	Phaser 6510DN	Phaser 6510DNI
Operating Systems	Windows®, 7, 8, 10, Server 20 Mac OS® version 10.5 and hi Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15 SUSE®	000, Server 2003, Server 2008, Server 2008 R2, Server	r 2012
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD SMB SMTP, Secure SMTP LDAP, Secure LDAP Bonjour® / Airprint® FTP Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP v2/3, WINS, DI	HCP Autonet, TLS, SNTP, MDNS	
Font Capability	136 PostScript fonts 88 PCL fonts		
Mobile Solutions and Mobile Device Apps			
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.		
Xerox [®] Global Print Driver [®]	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.		
Google Cloud Print [™]	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.		
Xerox® Print Service Plug-in for Android [™] (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.		
Xerox® Wireless Print Solutions Adapter (Optional)	The Xerox® Wireless Print Solutions Adapter seamlessly connects your Xerox® printer or MFP to modern mobile and desktop workflows, regardless of your office environment. For more information, visit www.xerox.com/WPSA		
Security	Phaser 6510N	Phaser 6510DN	Phaser 6510DNI
Security Features	Secure HTTPS (TLS) IPsec 802.1x Authentication S/MIME IP Filtering Secure Print SNMP v3 LDAP (SASL)		
Device Management			
Xerox® CentreWare® Web			
	whether running Windows • Works with any SNMP-mar	s or UNIX or any other operating system naged printer from any manufacturer	rowser-based device management from any workstation, shooting, and device upgrades, as well as basic accounting
Xerox® Embedded Web Server - Integrated D	evice Web Page		
Device Status	Web server embedded • Tray status/contents • Consumables status		
Print Queue Viewing	Complete job print queue m	anagement—hold, release, promote and delete	
Job Submission	Print-ready files (PS, PCL®, PC Output feature selection	DF, XPS, JPEG)	
Device Administration	Allows simple, remote install	ation setting of configuration options and managem	nent of the device.

Xerox® Embedded Web Server - Integrate	ed Device Web Page			
Browsers	Microsoft® Internet Explorer 11 Microsoft Edge™ 38 Mozilla™ Firefox® 48 Apple® Safari® 9.1 Google Chrome™ 52 Opera™ 39			
Remote Print Services				
Xerox® MeterAssistant® Service	Automates the process of collecting and submitti consumingend-user involvement and ensures the	ing meter reads for tracking and billing of Xerox® device usage. Eliminates the need for timeat meter reads are submitted to Xerox on time.		
Xerox [®] SuppliesAssistant [®] Service	Automatically orders supplies for Xerox® output d	evices based on actual usage, eliminating the need to manually manage supplies inventory.		
Maintenance Assistant		Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.		
What's In The Box				
	 Phaser 6510 Colour Printer Standard Capacity Print cartridge: One of each (Cyan, Magenta, Yellow: 1,000 print capacity⁶; Black: 1,500 print capacity⁶ Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord 			
Supplies and Accessories	Quantity	Part Number		
Supplies				
Extra-High Capacity Print Cartridges	Cyan: 4,300 standard pages ⁴ Magenta: 4,300 standard pages ⁴ Yellow: 4,300 standard pages ⁴	106R03693 106R03694 106R03695		
High Capacity Print Cartridges	Black: 5,500 standard pages ⁴ Cyan: 2,400 standard pages ⁴ Magenta: 2,400 standard pages ⁴ Yellow: 2,400 standard pages ⁴	106R03488 106R03485 106R03486 106R03487		
Standard Capacity Print Cartridges	Black: 2,500 standard pages ⁴ Cyan: 1,000 standard pages ⁴ Magenta: 1,000 standard pages ⁴ Yellow: 1,000 standard pages ⁴	106R03484 106R03481 106R03482 106R03483		
Drum Cartridge	Black: 48,000 pages ⁵ Cyan: 48,000 pages ⁵ Magenta: 48,000 pages ⁵ Yellow: 48,000 pages ⁵	108R01420 108R01417 108R01418 108R01419		
Waste Cartridge	30,000 pages ⁵ 108R01416			
Accessories				
550-sheet Paper Tray		097S04765		
Wireless Network Adapter		497K16750		

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
² Expected regular monthly throughput.
³ Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.
⁴ Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.
⁵ Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.



Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.



For more information, visit us at www.xerox.com/office