

# Xerox<sup>®</sup> WorkCentre<sup>™</sup> 5945/5955 Multifunction Printer

WorkCentre 5900 series multifunction printers are built on Xerox® ConnectKey® technology. These simple-toimplement systems give you real, practical solutions that easily streamline how you communicate, process and share important information, simplify complex paper-driven tasks, and drive down costs while keeping your data secure.





WorkCentre 5945 shown with Office Finisher

WorkCentre 5955 shown with Office Finisher with Booklet Maker

|  | WorkCentre 5945 shown with Office Finisher   | WORKCENTRE 5955 shown with Office Finisher with Booklet Maker                                  |  |
|--|--|--|--|
| System Specifications  | WorkCentre 5945 WorkCentre 5955  |  |  |
| Simplex Speed<br>A4 / 8.5 x 11 in. (LEF)<br>A4 to B4 / 8.5 x 13 to 8.5 x 14 in. (SEF)<br>A3 / 11 x 17 in. (A3 SEF) (Bypass Tray<br>will reduce speed by 10 to 20%) | 45 ppm<br>36 ppm<br>31 ppm   | 55 ppm<br>36 ppm<br>31 ppm   |  |
| Auto Duplex Speed<br>A4 / 8.5 x 11 in. (LEF)<br>A3 / 11 x 17 in. (SEF)   | Up to 45 ipm / 2-sided 22.5 sheets per minute<br>Up to 31 ipm / 2-sided 15.5 sheets per minute   | Up to 55 ipm / 2-sided 27.5 sheets per minute<br>Up to 31 ipm / 2-sided 15.5 sheets per minute |  |
| Monthly Duty Cycle <sup>1</sup>  | Up to 175,000 pages  | Up to 200,000 pages  |  |
| Recommended Average Monthly<br>Print Volume <sup>2</sup>   | Up to 20,000 pages   |  |  |
| Hard Drive / Processor / Memory  | Minimum 250 GB / 1 GHz Dual-core / 2 GB system   |  |  |
| Connectivity   | 10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Optional Wi-Fi  | i (with Xerox® USB Wireless Adapter)   |  |
| Controller Features  | Unified Address Book, Remote Control Panel, Online Support, Configuration Clo  | ning   |  |
| Copy and Print   |  |  |  |
| Copy and Print Resolution  | Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 dpi, 256 shades of grey  |  |  |
| First-copy-out Time  | As fast as 3.7 seconds from the Platen / 7.6 seconds from the Automatic Document Feeder  |  |  |
| Page Description Languages   | Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional)   |  |  |
| Print Features   | Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring  |  |  |
| Mobile Printing  | Apple® AirPrint, Xerox® PrintBack, Xerox® Mobile Print (Optional), Xerox® Mobile Print Cloud® (Optional)   |  |  |
| Scan   |  |  |  |
| Standard   | Destinations: Scan to Mailbox; Scan to USB, Scan to Email, Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearised PDF   |  |  |
| Optional   | Software Packages: ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® Professional, other solutions available through various Xerox Alliance Partners   |  |  |
| Fax  |  |  |  |
| Standard Features  | Internet Fax, Fax Build Job, Network Server Fax Enablement   |  |  |
| Optional Features  | One-line and two-line options, includes LAN Fax, Fax Forward to Email or SMB, Walk-up Fax  |  |  |
| Security   |  |  |  |
| Standard Features  | McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions |  |  |
| Optional Features  | McAfee Integrity Control, Xerox Secure Access Unified ID System®, Smart Card Enablement Kit (CAC/PIV/.NET)   |  |  |
| Accounting   |  |  |  |
| Standard Features  | Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting   | g Enablement   |  |
| Optional Features  | Equitrac Express®, Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox®<br>Business Innovation Partners  |  |  |

| Device Specifications  |  |  |   |                                   |
|--|--|--|---|-----------------------------------|
| Control Panel Languages  | US English, International English, Inter   | national French, Italian, German, Intern   | ational Spanish, Dutch, Brazilian Portug  | uese, Swedish, Norwegian, Danish, |
|  | Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian, Catalan  |  |   |                                   |
| Accessories  |  |  |   |                                   |
| Optional   | Envelope Tray Kit (Inserts into Tray 2)<br>Office Finisher<br>Office Finisher with Booklet Maker<br>Hole Punch for Office Finisher<br>Convenience Stapler (includes Work Surface)<br>Smart Card Enablement Kit<br>Xerox Secure Access Unified ID System® (with USB Card Reader)<br>Walk up Fax (One- or Two-line options, includes LAN Fax)<br>ScanFlowStore®<br>Xerox® USB Wireless Adapter<br>McAfee® Integrity Control Enablement Kit<br>XPS Print Option Kit |  |   |                                   |
| Foreign Device Interface (FDI)<br>(Optional)   | Also known as Auxiliary Access Device,   | this is an interface to third party access | control devices, such as coin machines o  | and card readers.                 |
| Electrical Requirements  |  |  |   |                                   |
| North America  | Voltage : 110-127 VAC +/- 10%<br>Frequency: 50/60 Hz +/- 5%, 15 A  |  |   |                                   |
| Europe   | Voltage : 220-240 VAC +/- 10%<br>Frequency: 50/60 Hz +/- 5%, 10 A  |  |   |                                   |
| Power Consumption  | WorkCentre 5945  |  | WorkCentre 5955                           |                                   |
| Running (Average)<br>Base Unit with Offset Catch Tray:<br>Base Unit with Office Finisher:<br>Base Unit with Office Finisher with<br>Booklet Maker: | 1,150 watts<br>1,230 watts<br>1,230 watts  |  | 1,250 watts<br>1,330 watts<br>1,330 watts |                                   |
| Standby Mode<br>Base Unit with Offset Catch Tray:<br>Base Unit with Office Finisher:<br>Base Unit with Office Finisher with<br>Booklet Maker:      | 45 watts<br>55 watts<br>55 watts   |  | 45 watts<br>55 watts<br>55 watts          |                                   |
| Sleep mode   | 3 watts  |  | 1   |                                   |
| Ready to Scan and Print<br>(from Power On)   | As fast as 230 seconds (3 minutes, 50  | seconds)                                   |   |                                   |
| Recovery from Low Power  | As fast as 4 seconds   |  |   |                                   |
| Recovery from Sleep  | As fast as 28 seconds  |  |   |                                   |
| Operating Environment  |  |  |   |                                   |
| Required Temperature Range   | 10° to 32° C / 50° to 90° F  |  |   |                                   |
| Required Relative Humidity   | 15% to 85%   |  |   |                                   |
| Sound Power Levels   | Operating 7.1 B(A), Standby: 5.0 B(A)  |  |   |                                   |
| Sound Pressure Levels  | Operating: 56 dB(A), Standby: 35 dB(A)   |  |   |                                   |
| Dimensions and Weight  | Width  | Depth                                      | Height                                    | Weight                            |
| Base Configuration with Internal<br>Tray   | 850 mm / 33.5 in.  | 665 mm / 26.2 in.                          | 1,150 mm / 45.3 in.                       | 113 kg / 249 lbs.                 |
| With Office Finisher   | 1,470 mm / 57.9 in.  | 665 mm / 26.2 in.                          | 1,150 mm / 45.3 in.                       | 142.5 kg / 314.5 lbs.             |
| With Office Finisher with Booklet<br>Maker   | 1,530 mm / 60.2 in.  | 665 mm / 26.2 in.                          | 1,150 mm / 45.3 in.                       | 158.5 kg / 349.5 lbs.             |
| Work Surface (does not add to overall width with Bypass Tray open)   | 285 mm / 11.2 in.  | -  | -   | -                                 |

| Certifications                     |  |
|------------------------------------|--|
|                                    | FCC Class A Compliant (US), ICES Class A Compliant (Canada)                          |
|                                    | CSA Listed (UL 60950-1, Second Edition)  |
|                                    | CB Certified (IEC 60950-1, Second Edition)   |
|                                    | ENERGY STAR®   |
|                                    | GOST<br>NOM  |
|                                    | Blue Angel   |
|                                    | Environmental Choice   |
|                                    | CE Marked  |
|                                    | Common Criteria (IEEE 2600.2 standard)<br>EPEAT                                      |
|                                    | GS Mark  |
|                                    | Citrix® Certified  |
|                                    | WHQL   |
|                                    | MEDITECH<br>Cerner   |
|                                    | To view the latest list of certifications, go to www.xerox.com/OfficeCertifications. |
| Paper Handling                     |  |
| Single-pass Automatic Document Fe  | eder   |
| Capacity <sup>3</sup>              | 200 sheets   |
| Speed (black and white and colour) | Up to 105 images per minute (ipm) (simplex)  |
| speed (order and write and colour) | Up to 200 ipm (duplex) black and white, up to 160 ipm (duplex) colour                |
| Paper Sizes Sensed                 | 125 x 138 mm to 297 x 432 mm / 4.9 x 5.4 in. to 11.7 x 17 in.                        |
| Weights                            | 50 gsm to 160 gsm / 13 lb. bond to 43 lb. bond                                       |
| Bypass Tray                        |  |
| Capacity <sup>3</sup>              | 100 sheets   |
| Sizes                              | Custom sizes: A6 to A3 / 4.25 x 5.5 in. to 11 x 17 in.                               |
| Weights                            | 60 to 216 gsm / 16 lb. bond to 80 lb. cover  |
| Туреѕ                              | Bond   |
| Types                              | Carbonless   |
|                                    | Card Stock   |
|                                    | Envelopes  |
|                                    | Hole punched<br>Index  |
|                                    | Labels   |
|                                    | Letterhead   |
|                                    | Plain<br>Preprinted  |
|                                    | Recycled   |
| Trays 1 and 2                      |  |
| Capacity <sup>3</sup>              | 500 sheets each  |
| Sizes                              | Custom Sizes from A5 to A3 / 5.5 x 8.5 in. LEF to 11 x 17 in. SEF                    |
| Weights                            | 60 to 200 gsm / 16 lb. bond to 53 lb. bond   |
| Types                              | Bond   |
| 13403                              | Card Stock   |
|                                    | Glossy   |
|                                    | Hole punched   |
|                                    | Index<br>Labels  |
|                                    | Letterhead   |
|                                    | Lightweight Card Stock   |
|                                    | Plain<br>Preprinted  |
|                                    | Recycled   |
|                                    | Transparencies (Tray 2 only)   |
| High Capacity Tandem Tray          |  |
| Capacity <sup>3</sup>              | Tray 3: 1,600 sheets   |
|                                    | Tray 4: 2,000 sheets   |
| Sizes                              | Standard Sizes: A4 / 8.5 x 11 in. LEF  |
| Weights                            | 60 to 216 gsm / 16 lb. bond to 53 lb. bond   |

| Турез  | Bond<br>Card Stock<br>Glossy   |
|--|--|
|  | Hole punched   |
|  | Index<br>Letterhead  |
|  | Lightweight Card Stock   |
|  | Plain<br>Preprinted  |
|  | Recycled   |
| Envelope Kit (Inserts into Tray 2)                 |  |
| Capacity <sup>3</sup>                              | Up to 50 envelopes   |
| Sizes  | #10 Commercial (9.25 x 4.125 in.), DL, C5  |
| Weights  | 75 to 90 gsm / 20 lb. bond to 24 lb. bond  |
| Total Capacity                                     |  |
| Device Total Capacity <sup>3</sup>                 | 8,700 sheets   |
| Finishing  |  |
| Centre Offsetting Tray                             |  |
| Capacity   | Up to 400 sheets of 80 gsm / 20 lb. bond   |
| Office Finisher (Optional)                         |  |
| Top Tray Capacity<br>Stacking Tray Capacity        | 250 sheets unstapled of 80 gsm<br>2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) |
| Top Tray Sizes<br>Stacking Tray Sizes              | A6 to A3 / 4.25 x 5.85 in. to 11 x 17 in.<br>A5 to A3 / 5.5 x 8.5 in. to 11 x 17 in.   |
| Weights  | 60 to 216 gsm / 16 lb. bond to 58 lb. bond   |
| Multiposition Stapling                             | 50 sheets of 80 gsm / 20 lb. bond  |
| Hole Punch (Optional)<br>North America:<br>Europe: | 2-3 Hole Punch<br>2-4 Hole Punch   |
| Office Finisher with Booklet Maker (               |  |
| Top Tray Capacity                                  | 250 sheets unstapled of 80 gsm   |
| Stacking Tray Capacity                             | 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)                                   |
| Top Tray Sizes<br>Stacking Tray Sizes              | A6 to A3 / 4.25 x 5.85 in. to 11 x 17 in.<br>A5 to A3 / 5.5 x 8.5 in. to 11 x 17 in.   |
| Weights  | 60 to 216 gsm / 16 lb. bond to 58 lb. bond   |
| Multiposition Stapling                             | 50 sheets of 80 gsm / 20 lb. bond  |
| Hole Punch (Optional)<br>North America:<br>Europe: | 2-3 Hole Punch<br>2-4 Hole Punch   |
| Booklet Making Capacity <sup>3</sup>               | 40 booklets (2-15 sheets per booklet – 80 gsm / 20 lb. or less)  |
| Booklet Making Sizes                               | A4 / 8.5 x 11 in. (SEF)<br>B4 / 8.5 x 14 in. (SEF)<br>A3 / 11 x 17 in. (SEF)   |
| Saddle-stitch Stapling                             | 2-15 sheets / 8 – 60 page booklet<br>60 to 90 gsm / 16 lb. bond to 24 lb. bond   |
| Folding  | 1-15 sheets / unstapled  |
| Convenience Stapler (Optional – Inc                | ludes Work Surface)  |
| Capacity <sup>3</sup>                              | 50-sheet stapling<br>5,000 staples<br>Requires a separate power outlet   |
| Сору   |  |
| First-copy-out Time                                | As fast as 3.7 seconds from the Platen / 7.6 seconds from the Automatic Document Feeder  |
| Sides (input:output)                               | 1-1, 1-2, 2-2, 2-1   |
| Quantity   | 1 to 9,999   |
| Resolution (max.)                                  | Scan: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 dpi, 256 shades of grey  |
| Reduction / Enlargement                            | Variable zoom from 25% to 400% in 1% increments  |
| Concurrency  | Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)  |

| Copy Feαtures                                    | Annotation and Bates <sup>™</sup> stamping (with colour capability and font size adjustment)<br>Authentication for Services<br>Auto Paper Select<br>Auto Ray Switching<br>Autoring Switching<br>Autoring Switching<br>Autoring Switching<br>Autoring Switching<br>Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built)<br>Collation<br>Collation<br>Covers (Front only, front and back, back only, printed inside and out: Blank or Printed)<br>Dividers (blank)<br>Edge Erase<br>Features Help (Intuitive text and graphic descriptions)<br>ID Card Copy<br>Image Quality Adjustments<br>Image Shift (with Auto Centre option)<br>Invert Image (negative or mirror image)<br>Large Job Interrupt<br>Multi-up (up to 15 columns by 15 rows)<br>Sample Set<br>Save Job Settings<br>Stapling<br>Transparencies |
|--|---|
| Xerox <sup>®</sup> Copier Assistant <sup>®</sup> | Xerox <sup>®</sup> Copier Assistant <sup>®</sup> (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox <sup>®</sup> Copier Assistant for free, visit www.xerox.com  |
| Print  |   |
| Print Resolution                                 | Up to 1200 x 1200 dpi, 256 shades of grey   |
| Print Feαtures                                   | Application Defaults<br>Banner Sheet Enable / Disable<br>Bi-directional Status<br>Cover Selection<br>Delay Print (specific time)<br>User Permissions<br>Image Options (Toner Saver, Resolution (Standard, High)<br>Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)<br>LAN Fax (requires optional Fax Kit)<br>Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size)<br>Overlays<br>Paper Selection by Attribute<br>Sample Set<br>Saved Job<br>Secure Print with Timed Deletion<br>Special Pages (exception page programming: covers, inserts, exception pages)<br>Store and Recall Driver Settings<br>Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)                                    |
| Print from USB                                   | Allows walk-up printing from Type A USB port on front panel<br>Supports direct printing from computer via Type B USB port<br>Supported file formats: PDF, JPEG, TIFF, PS, XPS4, PCL   |
| Operating Systems                                | Microsoft® Windows® XP SP3 (32- and 64-bit)<br>Windows Server 2003 (32- and 64-bit)<br>Windows Server 2008 and R2 (32- and 64-bit)<br>Windows Server 2012 and R2<br>Windows Vista SP2 (32- and 64-bit)<br>Windows 7 (32- and 64-bit)<br>Windows 8.1 (32- and 64-bit)<br>Mindows 8.1 (32- and 64-bit)<br>Mac OS 10.7, 10.8, 10.9<br>Linux® Rednat® Fedora® Core 19 x86<br>Ubuntu® 13.10 x64<br>openSUSE® 13.1 x64  |
| Network Protocols                                | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD<br>NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)<br>AppleTalk®: EtherTalk®<br>Microsoft Windows Networking over IP<br>Apple® Bonjour®<br>IPv6<br>Secure FTP<br>Most protocols not in use can be disabled   |
| Administrative Protocols                         | DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP  |

| Fonts  | PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support)<br>PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts  |  |
|--|--|--|
| Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup><br>(X-MED) | Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.   |  |
| Xerox <sup>®</sup> Global Print Driver <sup>®</sup>              | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consiste easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.   |  |
| Xerox <sup>®</sup> Pull Print Driver                             | Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.   |  |
| Print Solutions  |  |  |
| Xerox® Mobile Print Cloud<br>(Optional)                          | Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.   |  |
| Xerox® Mobile Print Solution<br>(Optional)                       | Xerox <sup>®</sup> Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox <sup>®</sup> Mobile Print<br>Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release<br>code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.   |  |
| Unified Address Book   |  |  |
| Features   | Services supported: Fax, Internet Fax, Email, Scan to<br>Maximum contacts: 5,000<br>Contacts: Supports 1 or more destinations<br>Favourites for quick access of fax numbers, emails, etc.  |  |
| Scan   |  |  |
| Concurrency  | Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)   |  |
| Input Speed  | Scan at up to 160 ipm colour scanning and 200 ipm black and white scanning – A4 / 8.5 x 11 in. (LEF)   |  |
| Resolution   | 72 x 72 dpi to 600 x 600 dpi<br>Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)   |  |
| Maximum Scan Area  | A3 / 11 x 17 in.   |  |
| Scan Template Management   | Support 250 scan templates<br>Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs<br>Confirmation sheet options   |  |
| Network Protocols  | sFTP, FTP, SMB, NetWare, HTTP, HTTPS   |  |
| File Compression   | Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW)<br>Black and white TIFF (G3MH, G4 MMR compression – single or multiple pages)<br>Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC))<br>Linearised PDF / PDF/A  |  |
| Document Management Fields<br>(Meta Data)                        | <ul> <li>Features only available in Network Scan to File Templates:</li> <li>1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations</li> <li>Customised fields viewed on user interface for variable data input</li> </ul>   |  |
| Scan Features  | Mixed Size Originals<br>Scan Build Job<br>Compression Quality / File Size Control<br>Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine)<br>Auto Background and Shadow Suppression<br>Size for Size (for mixed size originals)<br>TWAIN Support / WIA Support<br>Bound Originals<br>Edge Erase<br>Reduction / Enlargement   |  |
| Scan to Email (Standard)   |  |  |
| Directory Access   | Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino)<br>Downloaded address list (comma-separated file format)   |  |
| Scan Features  | <ul> <li>Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options</li> <li>Scan to Email S/MIME Encryption</li> <li>Email signing (requires Smart Card option)</li> <li>Auto send to self</li> </ul>  |  |
| Network Scanning – Software Solu                                 | itions   |  |
| Xerox® Scan to PC Desktop®<br>Professional (Optional)            | <ul> <li>A desktop offering that provides advanced document imaging, archiving, editing and organisation tools:</li> <li>PaperPort Professional image viewing and file management software <ul> <li>Complete PDF functionality</li> <li>Secure PDF workflow of all scanning applications</li> </ul> </li> <li>OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion</li> <li>Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability</li> </ul> |  |

| Xerox® ConnectKey® for<br>SharePoint® (Optional)                    | Xerox <sup>®</sup> ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox <sup>®</sup> MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.  |  |
|---|---|--|
| Xerox® ConnectKey Share to Cloud<br>(Optional)                      | Xerox <sup>®</sup> ConnectKey Share to Cloud provides organisations with powerful, easy and secure document scanning capabilities that connect your Xerox <sup>®</sup> MFP to popular cloud services and email, such as Google Docs <sup>™</sup> , SalesForce.com, Office 365 and Dropbox <sup>™</sup> and gives employees anytime, anywhere access to their most important documents using mobile devices.   |  |
| Xerox® ConnectKey® for<br>DocuShare® (Optional)                     | Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP).  |  |
| Security  |   |  |
| Features  | <ul> <li>Expanded Authentication <ul> <li>Network authentication to access device and/or device services via-Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008), NDS, LDAP</li> <li>Xerox® Secure Access</li> <li>Local Authentication (internal database)</li> <li>Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) / .NET</li> </ul> </li> <li>Secure Data <ul> <li>Digitally signed PDF (when using Smart Card authentication)</li> <li>Encrypted / Password Protected PDF (Email and Network Scan Templates only)</li> <li>Secure Print (up to 10 digit PIN or Network Authentication)</li> <li>Incrypted / Password Protected PDF (Email and Network Scan Templates only)</li> <li>Secure Print (up to 10 digit PIN or Network Authentication)</li> <li>Immediate Image Overwrite</li> <li>On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk</li> <li>-FIPS 140-2 256 bit Hard Disk Encryption</li> </ul> </li> <li>Expanded Authorisation <ul> <li>Saccess based on network credentials</li> <li>Authorisation per user per service</li> <li>User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver</li> </ul> </li> <li>Secure Network Access</li> <li>IP Filter, IPsec, IPv6, SSL v30, SMNPv3, HTTPS, 802.1X, Cisco® TrustSec Identity Services Engine integration (optional), Device Security <ul> <li>McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional)</li> <li>Common Criteria Certification ISO 15408</li> </ul> </li> </ul> |  |
| Xerox Secure Access Unified ID<br>System <sup>®</sup><br>(Optional) | Xerox Secure Access Unified ID System integrates your Xerox® multifunction printers with your existing employee/student ID PIN or badge providing a flexible<br>and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction<br>printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job.<br>For more information, go to www.office.xerox.com/software-solutions   |  |
| Fax   |   |  |
| Network Server Fax Features Compatibility                           | ITY (CCITT) group 3   |  |
| Maximum Scan Area   | Various Xerox® Business Innovation Partner Solutions A3 / 11 x 17 in.   |  |
| Fax Send Features   | One- or two-sided scanning (up to A3 / 11 x 17 in.)<br>Add to send list (50 numbers maximum)<br>Build Job, Favourites, Delay send (specific time) Original type (photo, text or photo and text)   |  |
| Fax Print Features  | One- or two-sided printing, staple, Secure Print  |  |
| Transmission Resolution   | Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi)<br>Fine: 200 x 200 dpi<br>Standard: 200 x 100 dpi  |  |
| Internet Fax Features   |   |  |
| Capability  | Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP)<br>Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients   |  |
| Address Directory Access  | Send: Multi-page TIFF, PDF, PDF/A<br>Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG   |  |
| Resolution  | 72 x 72 dpi to 600 x 600 dpi<br>Bit Depth: 1-bit (black and white)  |  |
| Network Protocols   | SMTP (send), POP3 (receive)   |  |
| Compliance  | ITU-T T.37 compliant  |  |
| Walk-up Fax Features (Optional (Cus                                 | tomer-installable) – 1 and 2 lines)   |  |
| Compatibility   | ITU (CCITT) Group 3   |  |
| Speed / Modems  | One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time<br>ATA analogue terminal adapter utilising T38 (optional)  |  |
| Compression / Speed   | MH/G3, MMR/SG3  |  |
| Resolution  | Walkup Send:         Standard: 200 x 100 dpi         Fine: 200 x 200 dpi         Superfine: 600 x 600 dpi         Receive:         Accepts all sizes  |  |

| Fax Send Features  | LAN Fax (fax from print driver)<br>Auto fax transmission reduction<br>Page-by-page job status at the machine<br>Delay start, Build Job, Favourites<br>Automatic memory resend<br>Automatic cover sheets<br>PSTN Fax<br>Device Address Book (up to 1,000 contacts)   |  |
|--|---|--|
| Fax Receive Features                                     | One- or two-sided printing<br>Stapled or unstapled<br>Receive print mode – Manual (size, margin, stock, header) / Auto<br>Output tray selection<br>Up to 200 password protected mailboxes<br>Secure receive<br>Receive timestamp<br>Auto answer delay   |  |
| Fax Forward  | Forward to Email or SMB Location<br>Fax forward on receive only   |  |
| Fax Reports  | Activity, Dial directory, Group directory, Transmission confirmation, Pending fax, Options report, On demand overwrite report, Mailbox report, Broadcast report   |  |
| Auto Dialing   | Speed Dials: 5,000 total (one- or two-line options)<br>Group Dials: Up to 200 groups with up to 400 recipients per group (one- or two-line options)<br>Auto Redial: Up to 14 attempts (per country requirements)<br>• 1 to 25 minute intervals<br>• Batch send (up to memory capacity)  |  |
| Device Management  |   |  |
| Management Support                                       | SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP<br>MIB access (IETF-MIBII RFC 1213), Host Resources<br>MIB RFC 2790, Printer MIB RFC 1759 v.2  |  |
| Xerox® CentreWare® Web                                   | <ul> <li>A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system:</li> <li>Works with any SNMP-managed printer from any manufacturer.</li> <li>Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> <li>Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher.</li> <li>CentreWare Integration available for Tivoli® NetView®, Unicentre TNG®, Microsoft Management Console (MMC), HP® OpenView®</li> </ul> |  |
| Novell NDPS/NEPS   | Server gateway application: centralised management tool.  |  |
| Xerox® Device Manager                                    | <ul> <li>Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:</li> <li>Device monitoring and troubleshooting</li> <li>Extensive reporting and discovery of new devices</li> <li>Usage collection, chargeback and billing capabilities</li> </ul>  |  |
| Xerox <sup>®</sup> Device Types for SAP<br>Environment   | Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions   |  |
| Xerox® SAP R/3 Intelligent Barcode<br>Utility (optional) | Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.office.xerox.com/software-solutions  |  |
| Xerox® Barcode Pro PS (optional)                         | Enables intelligent PostScript printing on Xerox <sup>®</sup> multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk.<br>Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at<br>www.office.xerox.com/software-solutions  |  |
| CentreWare Internet Services – Integ                     | grated Web Pages Provided by the Device   |  |
| Device Status  | Web server embedded in Network Controller:<br>• Tray status/contents<br>• Consumables status<br>• Alerts  |  |
| Job Submission   | Print ready files: PS, PCL, TIFF, PDF, JPG, XPS <sup>4</sup> , TXT, PRN<br>Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination)<br>Delivery options (Immediate, sample set, delay and secure, Save job or reprint)  |  |
| Device Administration                                    | Allows simple, remote installation setting of configuration options and management of the device  |  |
| Browsers   | Internet Explorer 7x, 8x, 9x<br>Safari 5.x<br>Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x<br>Opera 11.x<br>Chrome 12   |  |
| Support  | Install print / scan drivers and online support available via web page  |  |
| Languages Supported                                      | International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or<br>Russian, Simplified Chinese, Korean, Japanese   |  |

| Remote Print Services   |  |  |                        |
|---|--|--|------------------------|
| Automatic Meter Reading (AMR)<br>(May not be available in all<br>regions)             | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-<br>consuming end-user involvement and ensures that meter reads are submitted to<br>Xerox on time.   |  |                        |
| Automatic Supplies<br>Replenishment (ASR)<br>(May not be available in all<br>regions) | Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory (may not be available in all countries).  |  |                        |
| Accounting  |  |  |                        |
| Xerox <sup>®</sup> Standard Accounting (Stando  |  |  |                        |
| Tracking  | Copy, Print, Fax, Scan and Email usage   |  |                        |
| Accounting  | Up to 2,497 User accounts (User ID)<br>Up to 500 General accounts (Client)<br>Up to 498 Group accounts (Department)  |  |                        |
| Features  | <ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file</li> </ul>  |  |                        |
| Accounting Options – Network Account  | unting – Third Party Enablement  |  |                        |
|   | <ul> <li>Comprehensive management and enterprise scale tracking and reporting c</li> <li>Numerous solutions are available through Xerox Business Innovation Partnet</li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>WorkCentre requests account authentication from third party server enabling</li> <li>Accept Authentication Login at control panel and pass to third party Network</li> </ul> | ers. For details visit www.xerox.co                            | om<br>accounts         |
| Supplies  | Description  | Quantity   | Part Number            |
| Toner Cartridge   | Includes 2 Toner Cartridges  | 88,000 pages <sup>5</sup><br>(44,000 pages each) <sup>5</sup>  | 006R01606              |
|   | Office Finisher with Booklet Maker – saddle-stitch stapling  | 2,000 per cartridge<br>(8,000 staples)                         | 108R01158              |
|   | Convenience Stapler<br>– Complete Cartridge<br>– Refill Cartridge  | 5,000 per cartridge<br>5,000 per cartridge<br>(15,000 staples) | 008R12964<br>008R12941 |
| Smart Kits®   |  |  |                        |
| Fuser Module  | North America:<br>Europe:  | 250,000 <sup>5</sup><br>250,000 <sup>5</sup>                   | 109R00847<br>109R00848 |
| Print Cartridge   | Includes xerographic drums, developer module, including dual auger ring,   | 200,0005   | 013R00669              |

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput

<sup>3</sup> Paper capacities are based on 75 gsm / 20 lb. stock; capacities will vary with different weight stocks.

<sup>4</sup> XPS option is required to print XPS files.

<sup>5</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area cover and and print mode.

Return spent imaging supplies through the Xerox<sup>®</sup> Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office.



©2014 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, ConnectKey®, Copier Assistant®, Global Print Driver®, Mobile Express Driver®, Scan to PC Desktop®, SuppliesAssistant®, WorkCentre and Xerox Secure Access Unified ID System® are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. 8/14