

Xerox® Phaser® 3330 Printer



System Specification		Phaser 3330
One-Sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm		Up to 42 ppm Up to 40 ppm Up to 34 ppm
Two-Sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm		Up to 21 ppm Up to 20 ppm Up to 17 ppm
Monthly Duty Cycle¹		Up to 80,000 pages / month
Recommended Average Monthly Print Volume²		2,000 to 4,500 pages
Processor		1 GHz
Memory		512 MB
Connectivity		USB 2.0 10/100/1000Base-T Ethernet Wi-Fi
Paper Handling		
Bypass Tray		
Capacity³		50 sheets
Sizes		Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm
Weights		16 lb. bond to 58 lb. cover / 60 to 220 gsm
Media Types		Archive Bond Card Stock Custom Envelopes Heavyweight Labels Lightweight Plain Preprinted Recycled Transparencies
Tray 1		
Capacity³		250 sheets
Sizes		Custom Sizes 3.9 x 5.8 in. to 8.5 x 14 in. / 99 x 147 mm to 216 x 356 mm
Weights		16 lb. bond to 43 lb. bond / 60 to 163 gsm
Media Types		Archive Bond Card Stock Heavyweight Lightweight Plain Recycled
Additional Tray		
Capacity³		550 sheets
Sizes		Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm
Weights		16 lb. to 43 lb. bond / 60 to 163 gsm

Xerox® Phaser® 3330 Printer

Additional Tray	
Media Types	Archive Bond Card Stock Heavyweight Lightweight Plain Recycled
Total Capacity	
Device Standard Capacity ³	300 sheets
Device Total Capacity ³	850 sheets
Paper Output	
Output Capacity ³	150 sheets
Automatic 2-Sided	Standard
Device Specification	
Electrical Requirements	
North America	110-127 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 7A
Europe	220-240 VAC +/- 10%, 50/60 Hz +/- 3 Hz, 5A
Power Consumption	
Operation ⁴	Maximum 700 watts
Standby Mode ⁴	Maximum 50 watts
Power Off Mode ⁴	Maximum 0.1 watts
Sleep Mode ⁴	Maximum 3.5 watts
Warm-up (from Sleep Mode)	As fast as 35 seconds
Operating Environment	
Required Temperature Range Storage Operating	32°F to 104°F / 0°C to 40°C 50°F to 90°F / 10°C to 32°C
Required Relative Humidity	20% to 80%
Sound Power Levels Operating Standby	54 dB(A) or less 26 dB(A) or less
Sound Pressure Levels Operating Standby	54 dB(A) or less 26 dB(A) or less
Dimensions and Weight (unpackaged)	
Phaser 3330	Width: 14.4 in. / 366 mm Depth: 14.4 in. / 366 mm Height: 11.4 in. / 289.6 mm Weight: 23.37 lb. / 10.6 kg
550-sheet Paper Tray	Width: 14.4 in. / 366 mm Depth: 17.9 in. / 454 mm Height: 5.7 in. / 146 mm Weight: 11.82 lb. / 5.36 kg
Dimensions and Weight (packaged)	
Phaser 3330	Width: 17.7 in. / 449.6 mm Depth: 17.7 in. / 449.6 mm Height: 15.9 in. / 403.9 mm Weight: 28.31 lb. / 12.84 kg
550-sheet Paper Tray	Width: 22.2 in. / 563 mm Depth: 19.6 in. / 497 mm Height: 11.2 in. / 285 mm Weight: 16.8 lb. / 7.62 kg

System Certification/Regulatory Compliance	
Certifications	FCC Part 15 Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition Section 508 NOM GS Mark EAC RoHS Directive 2011/65/EU WEEE Directive 2012/19/EU Citrix™ Certified Cerner (undergoing evaluation) Apple® AirPrint® 1.5 certification Google Cloud Print™ 2.0 Certification Mopria® certified Wi-Fi Alliance Certified Blue Angel MEDITECH ENERGY STAR® ECOLOGO® EPEAT (United States) To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .
Print	
First-Page-Out Time	As fast as 6.5 seconds (printing from USB); As fast as 9.5 seconds from print driver
Resolution	Up to 1200 x 1200 dpi image quality
Page Description Languages	PostScript 3 compatible PCL® 5e, 6 PDF Direct TIFF JPEG
Maximum Print Area	4 mm from all edges
Print Features	Watermarks Collation Automatic Two-sided Printing N-up Poster Booklet Print Custom Page Size Fit to Page Scaling Draft Mode Earth Smart Printing Print from USB Job Scheduling Print from Local Drive Save Save and Print
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL
Operating Systems	Microsoft® Windows® Vista and later Mac OS™ 10.8.x and later Various Linux® and Unix distributions
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Bonjour® / Airprint® IPv6 Secure FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP
Font Capability	136 PostScript fonts 111 scalable PCL fonts 1 Bitmap PCL font

Mobile Solutions and Mobile Device Apps																							
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.																						
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.																						
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.																						
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.																						
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to ConnectKey-enabled multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.																						
Security																							
Security Features	Secure HTTPS (SSL/TLS) Secure IPP SSL IP Filtering IPv6 SNMP v3 IPsec WEP (64-/128-bit) WPA2-PSK (AES) WPA / WPA2-Personal WPA / WPA2-Enterprise																						
WiFi Security																							
	<table border="1"> <thead> <tr> <th>Authentication Method</th> <th>Encryption</th> </tr> </thead> <tbody> <tr> <td>Open</td> <td>WEP 64 / 128-bit ASCII / HEX</td> </tr> <tr> <td>WPA PSK</td> <td>TKIP</td> </tr> <tr> <td>WPA PSK / WPA2 PSK</td> <td>AES</td> </tr> <tr> <td>WPA Enterprise</td> <td>TKIP</td> </tr> <tr> <td>WPA Enterprise / WPA2™ Enterprise</td> <td>AES</td> </tr> <tr> <td>WPA Enterprise Authentication Method options:</td> <td></td> </tr> <tr> <td>• PEAPVO MS-CHAPV2</td> <td></td> </tr> <tr> <td>• EAP-TLS</td> <td></td> </tr> <tr> <td>• EAP-TTLS PAP</td> <td></td> </tr> <tr> <td>• EAP-TTLS CHAP</td> <td></td> </tr> </tbody> </table>	Authentication Method	Encryption	Open	WEP 64 / 128-bit ASCII / HEX	WPA PSK	TKIP	WPA PSK / WPA2 PSK	AES	WPA Enterprise	TKIP	WPA Enterprise / WPA2™ Enterprise	AES	WPA Enterprise Authentication Method options:		• PEAPVO MS-CHAPV2		• EAP-TLS		• EAP-TTLS PAP		• EAP-TTLS CHAP	
Authentication Method	Encryption																						
Open	WEP 64 / 128-bit ASCII / HEX																						
WPA PSK	TKIP																						
WPA PSK / WPA2 PSK	AES																						
WPA Enterprise	TKIP																						
WPA Enterprise / WPA2™ Enterprise	AES																						
WPA Enterprise Authentication Method options:																							
• PEAPVO MS-CHAPV2																							
• EAP-TLS																							
• EAP-TTLS PAP																							
• EAP-TTLS CHAP																							
Device Management																							
Xerox® CentreWare® Web																							
Device Status	Web server embedded <ul style="list-style-type: none"> • Tray status/contents • Consumables status 																						
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete																						
Job Submission	Print-ready files (PS, PCL®5c/6, PDF, TIFF) Output feature selection																						
Device Administration	Allows simple, remote installation setting of configuration options and management of the device.																						
Browsers	Microsoft® Internet Explorer 6, 7 Firefox® 2., 3 Safari® 3.0																						
Xerox® CentreWare® Internet Services – Integrated Device Web Page																							
	<ul style="list-style-type: none"> • A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. 																						
Remote Print Services																							
Xerox® MeterAssistant® ServiceAutomated Meter Reading (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.																						
Xerox® SuppliesAssistant® ServiceAutomated Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.																						

Xerox® Phaser® 3330 Printer

Remote Print Services		
Maintenance Assistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox®, allowing for problems to be solved faster with increased uptime.	
What's In The Box		
	<ul style="list-style-type: none"> • Phaser 3330 Printer • Standard Capacity Print cartridge: 2,600 pages⁵ • Software and Documentation CD (with Safety, Regulatory, Recycling and Disposal Guides), Print Drivers and Warranty Statement • Installation Guide • Quick Use Guides • Power cord 	
Supplies and Accessories	Quantity	Part Number
Supplies		
Extra-High Capacity Print Cartridges	15,000 standard pages ⁵	106R03623
High Capacity Print Cartridges	8,500 standard pages ⁵	106R03621
Drum Cartridge	30,000 standard pages ⁶	101R00555
Accessories		
550-sheet Paper Tray	097N02254	
Near Field Communication (NFC) Enablement Kit	097N02255	
Card Reader Enablement Kit (without Card Reader)	497K18010	

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput.

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

⁵ Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

⁶ Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

Xerox® Phaser® 3330 Printer

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme.
For more information, visit www.xerox.com/about-xerox/recycling.



©2016 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, Global Print Driver®, MeterAssistant®, Mobile Express Driver®, SuppliesAssistant®, and Phaser® are trademarks of Xerox Corporation in the United States and/or other countries. Mopria is a trademark of the Mopria Alliance. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice.
9/16 BR19338 333SS-011A