

Specifications



Xerox 2101



Designed for your environment...
Engineered for productivity

The Xerox 2101 Digital Copier/Printer
with Fiery EX2101 Controller



The Xerox 2101 has unprecedented processing power, full color scanning capabilities, advanced copy and print functionality, and robust and modular finishing options to enable every user to effortlessly create professional quality documents.



For more information on the Xerox 2101, call **1-800 ASK XEROX** or visit us on the Web at: www.xerox.com

Specifications

Print Engine

- Xerographic Engine
- Print speed up to 101 ppm (8.5" x 11" / A4)
- FCOT: 4.2 seconds
- Simplex or duplex printing
- Laser raster output at 600 x 600 dpi

Copy Server

- 60 GB hard drive
- Maximum 6,000 page storage
- Maximum 240 document storage
- Maximum 1,000 pages in a document

Document Handler

- 50 sheet Duplex Automatic Document Feeder
- Throughput sizes: 5.8" x 8.27" to 11" x 17" (A5 to A3)
- Throughput weights:
Simplex: 12 to 32 lb. bond (38 to 128 gsm)
Duplex: 13 to 28 lb. bond (50 to 110 gsm)

Scanner

- 50 ipm black and white scanning
- Full color scanning
- 12 ipm color scanning at 400 dpi
- 24 ipm color scanning at 200 dpi
- Scans in industry standard TIFF or PDF
- Scan to Email
- Scan to Network File Server
- Scan directly to other 2101s

Throughput Materials

Stock weights

- Tray 1: 18 lb. to 28 lb. bond (64 to 105 gsm)
- Trays 2, 3, 4: 18 lb. to 32 lb. bond (64 to 128 gsm)
- Tray 5 Multi-Sheet (Bypass Tray): 18 lb. bond to 80 lb. cover (64 to 220 gsm)
- Tray 6 High Capacity Feeder: 15 lb. to 32 lb. bond (56 to 128 gsm)
- Tray 7 Interposer: 15 lb. bond to 80 lb. cover (56 to 220 gsm)

Paper Input Capacity

(sheet capacity all at 20 lb./75 gsm)

- Tray 1: 500 sheets (8.5" x 11")
- Trays 2, 3, 4: 550 sheets (7.125" x 10" to 12" x 18")
- Tray 5 Bypass Tray: 130 sheets (4" x 6" to 12" x 18")
- Tray 6 High Cap Feeder: 3,600 sheets (8.5" x 11")
- Tray 7 Interposer: 175 sheets (8.5" x 11" to 11" x 17")

Standard Interposer

- Inserts pre-printed offset and xerographic color documents in a post fuser manner

Finisher Choices

Stapler Finisher

- 3 position single or dual 100 sheet stapling
- 3 hole punch
- Output capacity of 3,000 sheets – 20 lb. (75 gsm)

Booklet Maker Finisher

- Automatically creates booklets of up to 15 pages and imposes them resulting in 60 imaged sides with saddle stitching and bi-fold
- Creates booklets from 11" x 17" (A3), 8.5" x 14" or 8.5" x 11" (A4) paper

Optional Folder

- C-fold and Z-fold
- Print on inside or outside of folded paper
- Folds 11" x 17" (A3) Z-fold for inserts

Printer Controller - Fiery® EX2101

- 866 MHz Intel Pentium III with 60 GB hard disk drive, 256 MB RAM, internal CD-ROM drive
- LCD Support
- Ethernet interface (10 MBTX/sec or 100 MBTX/sec)
- Fiery Advance Controller Interface (FACI) kit (optional)
- monitor, keyboard, mouse
- Command Workstation™ for centralized job management
- Built-in NetWise™ Networking Management
- Fiery WebTools™ for remote management via standard internet browsers
- Fiery Downloader™ for downloading PS, PDF and EPS files and fonts
- Fiery FreeForm™ for variable data printing
- DocBuilder™ Pro™ for document mgmt. (optional)
- Preview, edit and assemble documents before RIPing
- Fiery Velocity™ (Optional – available through 3rd party) for load balancing and color splitting

Client Environments Supported

- Windows 98 / ME / 2000 / XP and NT 4.0
- Macintosh OS 8.0x / 8.1x / 8.5x / 9.0x / 10.2 (in native mode)

PDLs and Data Formats

- Adobe PostScript Level 3
- PDF
- PCL 5e
- TIFF
- ASCII

Connectivity – Native Network Environments

- TCP/IP (Ethernet)
- AppleTalk (Ethernet only)
- Novell (IPX/SPX and Ethernet II only)

Electrical Requirements

- Print Engine:
- 208-240 VAC, 60 Hz, 15 amp service
- KVA Rating: 2.4KVA (operating)
- Agency certification: UL, FCC
- Printer Controller (Fiery EX2101):
- Auto voltage sensing: 115-120 VAC or 200-240 VAC +10%, 50-60 Hz

Dimensions and Weight

Width	Depth	Height	Weight
Xerox 2101 with Stapler Finisher, & Copy Server			
82.9" (2105 mm)	30.7" (780 mm)	56" (1423 mm)	758 lbs. (344 kg)
Xerox 2101 with Booklet Finisher, & Copy Server			
83.7" (2125 mm)	30.7" (780 mm)	56" (1423 mm)	825 lbs. (374 kg)
Xerox 2101 with Stapler Finisher, & Copy Server & HCF			
102.6" (2605 mm)	30.7" (780 mm)	56" (1423 mm)	886 lbs. (402 kg)
Xerox 2101 with Booklet Finisher, & Copy Server & HCF			
103.3" (2625 mm)	30.7" (780 mm)	56" (1423 mm)	952 lbs. (432 kg)
Folding Unit			
7.9" (200 mm)	32.5" (825 mm)	56" (1423 mm)	66 lbs. (30 kg)
Fiery Unit			
9.1" (230 mm)	18.1" (460 mm)	20.1" (510 mm)	22 lbs. (10 kg)

Space Requirements

Configurations for Xerox 2101	Width (in.)	Depth (in.)
Xerox 2101 with Stapler Finisher, & Copy Server	101.8" (2585 mm)	78" (1981 mm)
Xerox 2101 with Booklet Finisher, & Copy Server	102.6" (2605 mm)	78" (1981 mm)
Xerox 2101 with Stapler Finisher, & Copy Server & HCF	129.3" (3285 mm)	78" (1981 mm)
Xerox 2101 with Booklet Finisher & Copy Server & HCF	130.1" (3305 mm)	78" (1981 mm)
Folding Unit (in addition to either configuration)	8" (200 mm)	-
Fiery Unit (in addition to either configuration)	33" (838 mm)	-



Features, configurations and options may vary by location.



XEROX

Worldwide Partner

©2003 Xerox Corporation. All rights reserved. XEROX®, The Document Company®, X® (stylized), and Xerox 2101 are trademarks of or licensed to Xerox Corporation. EFI®, Fiery®, Fiery FreeForm™, Velocity, Command WorkStation™, NetWise™, WebTools™, and DocBuilder™ Pro™ are trademarks or registered trademarks of Electronics For Imaging, Inc. Macintosh®, Mac®, and AppleTalk® are trademarks or registered trademarks of Apple Computer, Inc. Adobe® and PostScript® are registered trademarks of Adobe Systems, Inc. Windows®, Windows® 95, Windows® 98, Windows® NT, Windows® 2000, Windows® ME and Windows® XP are trademarks of Microsoft® Corporation. Product appearance, build status and/or specifications are subject to change without notice. The Xerox Total Satisfaction Guarantee applies to equipment under a Xerox warranty or a Full Service Maintenance Agreement and is subject to certain conditions. 08/03. 610P717080