

# Product Safety Data Sheet

## Phaser 7500



### PRODUCT DESCRIPTION

Phaser 7500 N/DN, DT, DX Colour Printer

	Standard	Certifying Body	Report Reference/ Licence
<a href="#"><u>ELECTRICAL &amp; MECHANICAL CERTIFICATION</u></a>	IEC60950-1 : 2005 [2 <sup>nd</sup> Edition] EN60950-1 : 2006	NEMKO	114194
<a href="#"><u>ELECTRO-MAGNETIC COMPATIBILITY</u></a>	2004/108/EC	XEROX	EMC7500.00

### HEAT OUTPUT

Plug in, Off Mode BTU/hr	Powersave BTU/hr	Standby BTU/hr	Running (Average) BTU/hr *
0	33	282	1956

### POWER

Plug in, Off Mode Watts	Powersave Watts	Standby Watts	Running (Average) Watts *
0	11	94	652

\* colour simplex printing

#### **Note:**

The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

### ENVIRONMENTAL LIMITATIONS

Relative Humidity (%):  
10 – 80

Ambient Temperature (°C):  
10 - 32

### LIGHT SOURCE

LED

### AUDIBLE NOISE

Tested in accordance with ISO7779 and declared in accordance with ISO9296

Operating Conditions	Sound Pressure (LpAd) dB(A)	Sound Power (LWAd) B(A)
Phaser 7500N		
Standby	26	4.2
Continuous	51	6.8

# Product Safety Data Sheet

## Phaser 7500



### CHEMICAL EMISSIONS

Tested in accordance with RAL UL-122

	Emission rate (mg/h)
Dust	<0.3
Total Volatile Organic Compounds	5.1
Ozone	<0.11

### PRODUCT DIMENSIONS

	Depth	Width	Height	<u>WEIGHT</u>
Phaser 7500N/DN	665 mm	640 mm	399 mm	66 kg
Phaser 7500DT	665 mm	640 mm	532 mm	79 kg
Phaser 7500DX	665 mm	640 mm	770 mm	99 kg

### SPACE REQUIREMENTS

Not applicable – desktop equipment

### ENVIRONMENTAL INFORMATION



#### **ENERGY STAR**

Products that carry the ENERGY STAR® label are designed to use less energy, help you save money on utility bills, and help protect the environment.