

Features	Phaser 6128MFP/N
Print Speed (Mono / Color)	16 / 12 ppm (A4)
Duty cycle	up to 40 000 pages/ month
First Page Out Time	As fast as 17 seconds colour / 14 seconds black and white
Processor	400 MHz
Language Support	PCL 6 emulation (host-based for Mac and Linux)
Resident Fonts	PCL: 81 TrueType
Memory (Std / Max)	384MB/ 384MB
Print Mode	Standard: 600 x 600 x 1 dpi
	Enhanced: 600 x 600 x 4 dpi
Color Standards	Pantone Colour Approved solid-colour simulations, Color Correction, ICC Profile, Colour Sync
Printer Management	Phaser Installer, CentreWare® IS Embedded Web Server, CentreWare Web, PrintingScout™, Email alerts
Connectivity	10/100BaseTx Ethernet, USB 2.0
Energy Star Compliant	Yes
Printer Drivers Support	Windows: 2000 (>SP3), 2003, 2008 Server, XP, Vista
	Mac OS: X version 10.3 or higher
	Linux (print only): Redhat, SuSe, TurboLinux 10 desktop
Productivity Tools for PCL Driver	Manual two-sided, Secure Print, Proof Print, RAM collation, Skip blank pages, N-up printing, Fit to new page size, Custom page size defaults, Booklet printing ¹ , Watermarks ¹ , Poster ¹ , Overlay ¹ , Toner remaining gauges, Draft mode (¹ Available on Windows/PCL driver only)
Paper Handling	
Two-Sided Printing	Manual
Auto Document Feeder	35 sheets
Input (# trays, total sheets)	2/251 (1 sheet MPT & 250 sheets on Tray 2)
Max Input / Output Tray Capacity	251 sheets / 150 sheets face down
Media sizes (ADF)	From 139.7 x 139.7 mm to 215.9 x 355.6 mm
Media sizes (MPT and Tray 2)	Letter, Legal, US Folio, Executive, A4, A5, B5 JIS, custom from 76.2 x 127 mm to 215.9 x 355.6 mm
Supported types of media	Plain paper, letter head, Pre-Punched, Thin Card Stock, Special, Thick Card stock, Labels, Envelopes

Features	Phaser 6128MFP/N
Media density	60gsm - 216gsm
Scan Features	
Optical resolution	1200 dpi
Scan Methods	USB Scan to Application, Network Scan to FTP Server, Network Scan to SMB Server, Network Scan to Email
Scan Resolution Max via USB	9600 Enhanced dpi
Scan Drivers via USB	Twain & WIA
Scan File Formats via USB	JPEG, TIFF, PDF & BMP
Scan Resolution Max via Network	600 dpi
Scan File Format via Network	JPEG, TIFF & PDF
Email Addresses:	Up to 100 email addresses, Up to 10 email group addresses with 10 addresses associated with each group
Copy Features	
First-page-out-time	As fast as 27 seconds colour / 18 seconds black and white
Copy resolution	600 x 600 dpi
Copy Document Types	Text, Photo & Mixed
Copy Features	Reduce/enlarge (25%-400%), N-up copying, poster, auto fit, cloning, collate, ID Card Copy
Walk Up Fax Features	
Fax Scan Resolution (mode: dpi)	Std : 200 x 100, Fine: 200 x 200, Super Hi Q: 400 x 400
Fax Features	Delayed Start, Broadcast Sending: up to 200 destinations, Secure Receive (requires pin)m Color Fax, Junk Fax Filter
Fax Compression Formats	MH, MR, MMR, JBIG, JPEG for Color Fax
Fax Address Book	Up to 200 Speed Dials, Up to 6 Group Dials
LAN Fax	
Fax Scan Resolution (mode: dpi)	Std : 200 x 100, Fine: 200 x 200, Super Fine: 400 x 400
Fax Features	Delay send, broadcast, zoom (25%-400%), auto fit, rotation, N-up, watermark*, address book
Phone Book	Up to 500 Speed Dial Numbers, Up to 500 Group Dial Numbers
Memory Specifications	
Memory	Standard / Maximum 384 MB
Power	
Line voltages	220-240 VAC \pm 10%

Features	Phaser 6128MFP/N
Frequency Range	50/60 Hz \pm 3 Hz
Power consumption	
Sleep Mode	< 18.4 W
Standby Mode (Fuser On)	< 60 W
During Printing	360 W
Environment	
Temperature:	Storage: -20° to 40° C; Operating: 10° to 32° C;
Operating	10 to 32° C (50 to 90° F)
Storage	0 to 35° C (32 to 95° F)
Humidity (RH)	10% to 85%
Acoustic Noise	
Sound Power Level (B) Sound	
Printing	6,22
Standby	3,03
Pressure (dBA)	
Printing	52,2
Standby	14,9
Physical Dimensions	
Print Engine	
Height	585 mm
Width	425 mm
Depth	507 mm
Weight	29 kg