

Xerox® WorkCentre® 7800 Series Color Multifunction Printer

WorkCentre 7800 series multifunction systems are powered by the Xerox® ConnectKey™ Controller. These simple-to-implement systems give you real, practical solutions that easily streamline how you communicate, process and share important information, simplify complex paper-driven tasks, and drive down costs while keeping your data secure.



System Specifications	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855	
Speed					
Color / Black-and-white	Up to 30 / 30 ppm	Up to 35 / 35 ppm	Up to 45 / 45 ppm	Up to 50 / 55 ppm	
Monthly Duty Cycle ¹	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages	
Recommended Average Monthly Print Volume ²	8,000 to 12,000 pages	10,000 to 15,000 pages	16,000 to 20,000 pages	18,000 to 22,000 pages	
Hard Drive / Processor / Memory	160 GB / 1.2 GHz / 2 GB syste	m plus 1 GB page memory			
Connectivity	10/100/1000Base-T Ethernet,	High-Speed USB 2.0 direct print	, Optional Wi-Fi (supported via t	hird-party adapter)	
Print and Copy Resolution	Up to 1200 x 2400 dpi image	quality (Print and Copy Outpu	ıt)		
Controller Features	Unified Address Book, Remote	e Control Panel, Online Support	, Configuration Cloning		
Optional Controller	EFI Server, EFI Productivity Bu	ndle, EFI Ethernet Hub			
Print					
First-print-out Time Color / Black-and-white	As fast as 13.2 / 11.1 seconds	As fast as 10.9 / 8.7 seconds	As fast as 11.0 / 8.6 seconds	As fast as 7.8 / 6.6 seconds	
Page Description Languages	Adobe® PostScript® 3™, PDF, P	CL® 5c / PCL 6 emulations, XM	L Paper Specification (XPS) (Op	rtional)	
Print Features	Print from USB, Secure Print, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring, Color By Words, Xerox® PrintBack				
Mobile Printing	Apple AirPrint™, Xerox® Mobile Print® (Optional), Xerox® Mobile Print Cloud® (Optional)				
Scan					
Standard Features	Scan to Network, Scan to Email, Scan to Folder, Scan to SMB or FTP, Text Searchable PDF, PDF/A, XPS, Linearized PDF, JPEG, TIFF, Scan to USB Memory Device, Single-touch Scanning				
Optional Features	ConnectKey for Sharepoint, ConnectKey Cloud, Xerox® Scan to PC Desktop® SE, Xerox® Scan to PC Desktop Professional, Over 500 options available through various Xerox® Business Innovation Partner Solutions				
Fax					
Standard Features	Internet Fax, Fax Build Job				
Optional Features			-line options, includes LAN Fax) ess Innovation Partner Solutior		
Security					
Standard Features	McAFee® Embedded, McAfee ePO Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408)2, Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions				
Optional Features	McAfee Integrity Control, Smart Card Enablement (CAC), Secure Access Enablement (Magstripe, Legic, Mifare, IND/EMM/HITAG)				
Accounting					
Features	Xerox® Standard Accounting (various Xerox® Business Innov	Copy, Print, Scan, Fax, Email), Nation Partner Solutions)	Network Accounting Enablemer	nt (options available through	

Device Specifications							
Control Panel Languages		tional French, Italian, German, urkish, Greek, Russian, Czech, P					
Accessories							
Optional	High Capacity Feeder Envelope Tray (Replaces Tray Integrated Office Finisher (op Office Finisher LX Booklet Maker for Office Finis Hole Punch for Office Finisher Professional Finisher Convenience Stapler (includes Smart Card Enablement Kit Xerox® Secure Access Unified EFI® Fiery Network Controller Foreign Device Interface Walk up Fax (One- or Two-line Xerox® Scan to PC Desktop® ScanFlowStore® Xerox® Unicode International Xerox® Mobile Print Solution Xerox® Mobile Print Xerox® PrintBack Wireless Kit McAfee Integrity Control Enal XPS Print Option Kit	her LX LX S Work Surface) ID System® (with USB Card Re coptions, includes LAN Fax) Print Kit	ader)				
Foreign Device Interface (FDI) (Optional)	Interface to third party access	Interface to third party access control devices, coin machines, card readers Support a variety of vending stations available through the Xerox® Custom Application Service					
Electrical Requirements							
North America	Voltage : 110 –127 VAC +/- 1 Frequency: 50/60 Hz +/- 3%,						
Europe	Voltage : 220-240 VAC +/- 10 Frequency: 50/60 Hz +/- 3%,						
Power Consumption	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855			
Running (Average)	643 watts / hour	690 watts / hour	763 watts / hour	862 watts / hour			
Standby Mode	62 watts / hour		112 watts / hour				
Low Power Mode	59 watts / hour		80 watts / hour				
Auto Off / Sleep mode	4.2 watts / hour (Default time	e to Sleep mode = 2 minutes)	4.8 watts / hour (Default time	e to Sleep mode = 2 minutes)			
Warm-up	194 seconds						
Low Power Recovery	< 9 seconds						
Operating Environment							
Required Temperature Range	50° to 82° F (10° to 28° C)						
Required Relative Humidity	15% to 85%	15% to 85%					
Sound Power Levels	Operating 6.8 B(A), Standby:	3.6 B(A)					
Sound Pressure Levels	Operating: 56 dB(A), Standby	: 18 dB(A)					
Dimensions and Weight	Width	Depth	Height	Weight			
Base Configuration	41.9 in. / 1,064 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	321 lbs. / 146 kg			
With Integrated Office Finisher (7830/7835 only)	44.4 in. / 1,129 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	348 lbs. / 158 kg			
With Office Finisher LX (with Booklet Maker)	65.6 in. / 1,666 mm	65.6 in. / 1,666 mm 27.9 in. / 709 mm 45.2 in. / 1,149 mm 403 lbs. / 183 kg					
With Professional Finisher	75.7 in. / 1,922 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	526 lbs. / 239 kg			
With Professional Finisher and High Capacity Feeder	75.7 in. / 1,922 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	590 lbs. / 268 kg			

Certifications				
	FCC Class A Compliant (US), ICES Class A Compliant (Car CSA Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition) ENERGY STAR® GOST NOM Blue Angel Environmental Choice CE Marked Common Criteria (IEEE 2600.2 standard) EPEAT GS Mark	ada)		
Paper Handling	WorkCentre 7830 WorkCentre 7835	WorkCentre 7845	WorkCentre 7855	
Duplex Automatic Docu	ment Feeder		'	
Capacity ³	110 sheets	130 sheets (Single-pass	s DADF)	
Speed	up to 70 image per minute black-and-white and color (simplex)		ute black-and-white and color (simplex) inute black-and-white and color (duplex)	
Paper Sizes Sensed	5.5 x 8.5 in. to 11 x 17 in. / A5 to A3			
Weights	16 lb. bond to 32 lb. bond / 50 gsm to 128 gsm			
Bypass Tray				
Capacity ³	100 sheets			
Sizes	Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in. / 89 x 98 mm to	320 x 483 mm		
Weights	16 lb. bond to 110 lb. cover / 55 to 300 gsm			
3 Tray Module (Total 2,1	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Cardstock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain Reloaded Preprinted Recycled Transparencies			
Capacity ³	Trays 1 – 4: 520 sheets each			
Sizes	Tray 1: Custom Sizes from 5.5 x 7.2 in. SEF to 11.7 x 17 in. SEF / 140 x 182 mm to 297 x 432 mmTrays 2–4: Custom Sizes from 5.5 x 7.2 in. SEF to 12.6 x 18 in. SEF / 140 x 182 mm to SRA3			
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm	16 lb. bond to 140 lb. index / 60 to 256 gsm		

T	Don't	
Types	Bond Card Stock	
	Card Stock Reloaded	
	Custom	
	Glossy Card Stock Glossy Card Stock Reloaded	
	Heavyweight Card Stock	
	Heavyweight Card Stock Reloaded	
	Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded	
	Hole punched	
	Labels	
	Letterhead Lightweight	
	Lightweight Card Stock	
	Lightweight Cardstock Reloaded	
	Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded	
	Plain	
	Plain Reloaded	
	Preprinted Recycled	
	Transparencies	
High Capacity Tandem Tray	y (Total 3,140 sheets) (Available with all configurations)	
Capacity ³	Tray 1: 520 sheets	
	Tray 2: 520 sheets Tray 3: 867 sheets	
	Tray 4: 1,133 sheets	
Sizes	Tray 1: Custom Sizes from 5.5 x 7.2 in. SEF to 11.7 x 17 in. SEF / 140 x 182 mm to 297 x 432 mm	
	Tray 2: Custom Sizes from 5.5 x 7.2 in. SEF to 12 x 18 in. SEF / 140 x 182 mm to 320 x 458 mm	
	Trays 3–4: Standard Sizes: 8.5 x 11 in. LEF / A4, JIS B5, Executive (7.25 x 10.5 in.)	
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm	
Types	Bond Card Stock	
	Custom	
	Glossy Card Stock	
	Hole punched Labels	
	Letterhead	
	Lightweight Card Stock	
	Lightweight Glossy Card Stock Plain	
	Preprinted	
High Capacity Feeder (HCF) (Optional)	
Capacity ³	2000 sheets	
Sizes	Standard Sizes: 8.5 x 11 in. / A4 LEF	
Weights	16 lb. bond to 140 lb. index / 55 to 256 gsm	
Envelope Tray (Optional - R		
Capacity ³	Up to 60 envelopes	
Sizes	#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, 6 x 9 in. Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm)	
Weights	20 lb. bond to 24 lb. bond / 75 to 90 gsm	
Total Capacity		
Device Total Capacity ³	5,140 sheets	
Finishing		
Output Trays (Standard)		
Stacking Trays³	Dual Offset Catch Tray – up to 250 sheets each Left-side Face up Tray – up to 100 sheets	
L		

Integrated Office Finisher	(Optional with 7830/7835)	
Stacking Tray	500 sheets of 20 lb. bond / 80 gsm - 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm - 11 x 17 in. / A3	
Sizes	3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm	
Weights	16 lb. bond to 80 lb. cover / 60 to 256 gsm	
Stapling	Single Auto stapling:50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)	
Office Finisher LX (Option	al)	
Capacity ³	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)	
Sizes	7.2 x 8.3 in. to 11.7 x 17 in. / 182 x 210 mm to 297 x 432 mm	
Weights	16 lb bond to 80 lb cover / 60 to 256 gsm	
Multiposition Stapling	50 sheets of 24 lb. bond / 90 gsm	
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch	
Booklet Maker for Office F	inisher LX (Score/Crease, Saddle-stitch Staple) (Optional)	
Capacity ³	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)	
Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF	
Saddle-stitch Stapling	2-15 sheets / 8 – 60 page booklet 16 lb bond to 24 lb bond / 60 to 90 gsm	
Score / Crease	1-15 sheets / unstapled	
Professional Finisher (Opti	onal)	
Capacity ³	Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 or 100 stapled sets of 11 x 17 in. / A3 / SRA3	
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling	
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm	
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported	
Hole Punch (Standard) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)	
Booklet Maker	Saddle-stitch 2 to 5 sheets of 24 lb. / 90 gsm or less Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, SRA3 supported	
Convenience Stapler (Option	onal - Includes Work Surface)	
Capacity ³	50-sheet stapling 5,000 staples Requires a separate outlet	

Сору	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
First-copy-out Time (Letter/A4-size, from Platen to Center Tray)	As fast as 13.2 seconds As fast as 11.1 seconds	As fast as 10.9 seconds As fast as 8.7 seconds	As fast as 11.0 seconds As fast as 8.6 seconds	As fast as 7.8 seconds As fast as 6.6 seconds
Sides (input:output)	1-1, 1-2, 2-2, 2-1			
Quantity	1 to 9,999			
Resolution (max.)	Scan at 600 x 600 dpi, outpu	t at 1200 x 2400 dpi		
Reduction / Enlargement	Variable zoom from 25% to	400% in 1% increments		
Concurrency	Program-ahead to allow job t	o be initiated while initial job is	s processed (Copy, Print, Fax ar	nd Scan)
Copy Features	Collation Automatic 2-sided/Duplex Auto Reduction & Enlargement to fit selected paper size Booklet Creation Stapling Large Job Interrupt Auto Paper Select Authentication for Services (i.e. Color Copy) Auto Tray Switching Features Help (Intuitive text and graphic descriptions) Image Quality Adjustments Edge Erase Single Color Image Shift (with Auto Center option) Annotation and Bates™ stamping (with color capability and font size adjustment) Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Dividers (blank) Multi-up (up to 15 columns by 15 rows) Invert Image (negative or mirror image) Sample Set Save Job Settings			
Xerox [®] Copier Assistant [®]	conjunction with a customer-	A) Software provides a PC-base supplied PC attached via the Ueyboard access to basic and adcom	SB port, this software supports	s text-to-speech, screen
Print	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
Print Resolution	Up to 1200 x 2400 dpi			
Print Features	Application Defaults Banner Sheet Enable / Disable Bi-directional Status Custom Color Options (Color By Words) Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, High, Enhanced) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout / Watermark (N-up (16), Multi-up, Booklet layout / finishing, Fit to new paper size) Overlays Paper Selection by Attribute Print to Fax (requires optional Fax Kit) Sample Set Secure Print Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Store File in Folder Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) TWAIN Print Driver			
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT			

Operating Systems	Microsoft® Windows® XP (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 (32- and 64-bit) Windows Vista (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Mac OS® 10.5, 10.6, 10.7, 10.8 Solaris 9, 10 HP UX 11v2 AIX 5 Redhat® Fedora Core 15-17 Redhat Enterprise 4 and 5 openSUSE® 11 and 12 Ubuntu®			
Network Protocols	NetWare: Bindery and NE AppleTalk®: EtherTalk®	ernet Printing Protocol, LPR/LPD, F OS IPX/SPX, NDPS®/NEPS (with Se orking over IP(Most protocols not	erver Gateway)), IPv4/IPv6,WSD
Administrative Protocols	DHCP, BOOTP, SNMP, WI	NS, DDNS, SLP® v2, HTTP, RARP,	DHCP Autonet, SSL, NTP	
Fonts		e printer and bitmap font (includ onts, 2 Multiple Master fonts	ing Cyrillic font support)	
Xerox® Mobile Express Driver® (X-MED)	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.			
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.			
Scan	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
Concurrency	Scan while the system is a scanned originals and pri	orinting, copying, or while it is trainting concurrent jobs)	nsferring scan to network or f	ax jobs(priority is for return of
Input Speed	Scan at up to 70 ipm colo and-white – 8.5 x 11 in. /	or scanning, up to 70 ipm black- A4 LEF	Scan at up to 160 ipm col black-and-white – 8.5 x 11	or scanning, up to 160 ipm 1 in. / A4 LEF
Resolution	72 x 72 dpi to 600 x 600 Bit Depth: 1-bit (black-an	dpi d-white), 8-bit (grayscale), 24-bit	(color)	
Maximum Scan Area	11 x 17 in. / A3			
Scan Template Management	Support 250 scan templa Create device specific Cer Confirmation sheet optio	ntreWare scan templates and sha	re via device cloning to other	MFPs
Network Protocols	FTP, SMB, NetWare, HTTF	P, HTTPs		
File Formats	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) JPEG XPS Encrypted / Password Protected PDF (for Workflow Scanning)			
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customized fields viewed on user interface for variable data input			
Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Original Type (Photo and Auto Background and Sho Size for Size (for mixed size	Text, Photo, Text, Map, Newspapadow Suppression	er / Magazine)	

Supported Scan Destinations (Standard)	Scan to Network Server Scan to USB Drive Scan to Email Scan to Client (SMB or FTP) Scan to Mailbox Scan to Secure FTP Scan to Home	
Supported Scan Destinations (Optional)	Scan to Application Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop (Professional and SE) SMARTsend® ScanFlowStore ScanSoft PaperPort ScanSoft OmniPage Various Xerox® Business Innovation Partner Solutions	
Authenticαtion	Supports Kerberos (UNIX / Windows Server 2003 / Windows Server 2008) SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008) NDS LDAP Xerox® Secure Access Unified ID System® Locally on device (internal database) Convenience Authentication (Off-the-shelf USB Card Reader Support), Smart Cards: CAC / PIV and .NET	
Scan to Email (Standard)		
Directory Access	Address list via LDAP (Exchange/Notes/Domino) Downloaded address list (comma-separated file format)	
Scan Features	 Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options Scan to Email s/MIME Encryption (with Smart Card option) Auto send to self 	
Network Scanning – Softw	vare Solutions	
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools: Nuance PaperPort Professional image viewing and file management software Complete PDF functionality Secure PDF workflow of all scanning applications Nuance OmniPage Pro Office (for desktop/client installation) — Professional OCR software for digital archiving and document conversion Image Retriever — provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability	
Xerox® SMARTsend® (Optional)	Server based document routing software that supports multiple scan-enabled multifunctional systems (up to 250 per server): • Enables transformation, distribution and routing of scanned documents – with features like LDAP and auto discovery • Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including searchable PDF, workflow settings, workflow summary) • Scan to File Destinations: email, Novell NetWare folder, network folder, SMB folder, FTP, Microsoft Exchange 2000 Web folders, Web URL, remote printers • Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint • Workflow initiation via device scanning user interface (template selection at device UI)	
Xerox® SMARTsend® Professional (Optional)	Everything in Xerox® SMARTsend, plus: • Workflow initiation via Paperware (Scan cover sheets) • Server-based Optical Character Recognition (OCR) • Adding Metadata • Scan to Internet fax file destination	

Security	
Features	Expanded Authentication
reatures	 Expanded Authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008), NDS, LDAP Xerox® Secure Access Local Authentication (internal database) Smart Card authentication -144k CAC/PIV Card Support (2048 bit certificate key), .NET Secure Data Digitally signed PDF (with Smart Card) Encrypted Scan to Email (with Smart Card) Password Protected PDF (via Workflow scanning; not Scan to Email) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorization SA access based on network credentials Authorization per user per service User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, SSL, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec integration (optional), Device Security McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, , McAfee Integrity Control Common Criteria Certification (pending)
Xerox® Secure Access Unified ID System® (Optional)	The Xerox® Secure Access Unified ID System USB card reader configuration eliminates the need for the Authentication Device (also known as the flat box controller). The USB card reader connects directly to the device controller eliminating the need for a second IP address. Provides Two-factor identification (card swipe + pin / password) with
	secure document release with Follow-You Printing® • For more information see http://www.office.xerox.com/software-solutions/xerox-secure-access/enus.html
Fax	
Network Server Fax Featur	es
Compatibility	ITY (CCITT) group 3 Various Xerox® Business Innovation Partner Solutions
Maximum Scan Area	11 x 17 in. / A3
Fax Send Features	One- or two-sided scanning (up to 11 x 17 in. / A3) Add to send list (50 numbers maximum) Build Job, Speed Dial, Delay send (specific time) Original type (photo, text or photo and text)
Fax Print Features	One- or two-sided printing, staple, Secure Print
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi
Internet Fax Features	
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
Address Directory Access	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)
Network Protocols	SMTP (send), POP3 (receive)
Compliance	ITU-T T.37 compliant
Walk-up Fax Features (Opt	ional (Customer-installable) – 1 and 2 lines)
Compatibility	ITY (CCITT) Group 3
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission timeISDN via third-party adapter
Compression / Speed	MH/G3, MMR/G4
	1

Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes	
Fax Send Features	LAN Fax (fax from print driver) Auto fax transmission reduction Page-by-page job status at the machine Delay start, Build Job, Favorites Automatic memory resend Automatic cover sheets PSTN Fax Device Address Book (up to 65,000 contacts)	
Fax Receive Features	One- or two-sided printing Stapled or unstapled Receive print mode – Manual (size, margin, stock, header) / Auto Output tray selection Junk Fax prevention Up to 200 password protected mailboxes	
Fax Forward	Forward to Email or SMB Location Fax forward on receive only	
Fax Reports	Activity, Dial directory, Group directory, Transmission confirmation, Pending fax, Options report, On demand overwrite report	
Auto Dialing	Speed Dials: 5,000 total (one- or two-line options) Group Dials: Up to 200 groups with up to 400 recipients per group (one- or two-line options) Auto Redial: Up to 14 attempts • 1 to 25 minute intervals • Batch send (up to memory capacity)	
Device Management		
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2	
Xerox® CentreWare® Web	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP, 2000 (Professional or Advanced Server) or Windows 2003 and Internet Explorer 6.0 and higher. CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView® 	
Novell NDPS/NEPS	Server gateway application: centralized management tool.	
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities	
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. http://www.office.xerox.com/software-solutions/sap-device-types-for-xerox-printers/enus.html	
Xerox® SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at http://www.office.xerox.com/software-solutions/sap-device-types-for-xerox-printers/enus.html	
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.xeroxofficesapsolutions.com	

CentreWare Internet Servi	ces – Integrated Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts		
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12		
Support	Install print / scan drivers and online support available via web page		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese		
Remote Services			
MeterAssistant [®]	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
SuppliesAssistant®	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.		
Accounting			
Xerox® Standard Accounti	ng (Standard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 499 Group accounts (Department)		
Feαtures	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via a CSV file 		
EFI Fiery Network Control	ler (Optional)		
Processor	2.60 GHz, Intel Core 2 Duo E5300		
Memory (ESS)	1 GB		
System Disk	160 GB		
Print Languages (PDL)	PostScript v 3019		
Features	Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management Job Preview Job Merge Change Job Properties PANTONE® Color Tables Expert Color Settings: Profile, Rendering and Simulation Color Profile Suite FreeForm — Variable Data capabilities Booklet Maker 4.0 — booklet wizard to create booklets Print from USB flash drive Paper Catalog Secure Erase EFI PrintMe		
Connectivity	10Base-T/100Base-TX/1000Base-T Ethernet		
Optional	SeeQuence Preview (Impose & Compose) Mini-bundle (Spot On, Auto Trapping, Hot folders, Virtual Print) Ethernet Hub		

Supplies			
Toner Cartridges (Metered) ⁴	Black	26,000 pages	006R01509
	Cyan	15,000 pages	006R01512
	Magenta	15,000 pages	006R01511
	Yellow	15,000 pages	006R01510
Toner Cartridges (Sold) ⁴	Black	26,000 pages	006R01513
	Cyan	15,000 pages	006R01516
	Magenta	15,000 pages	006R01515
	Yellow	15,000 pages	006R01514
Transfer Belt Cleaner	1 Assembly	160,000 pages	001R00613
Second Bias Transfer Roll	1 Assembly	200,000 pages	008R13064
Staple Cartridges	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	for Office Finisher LX Booklet Maker (8 cartridges per carton)	2,000 each cartridge	008R12897
	for Professional Finisher Booklet Maker (4 cartridges per carton)	5,000 each cartridge	008R12925
Staple Refills	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill	008R12941
Smart Kits®			
Drum Cartridge	1 Cartridge per Color	125,0004	013R00662
Waste Toner Container	1 Cartridge	43,0004	008R13061

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Our products allow use of papers certified by the FSC, PEFC and SFI, and those made with post consumer recycled content. For more information regarding our entire line of paper and specialty media, contact your Xerox® representative or visit us at www.xerox.com/supplies.

Return spent imaging supplies through the Xerox® Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling/enus.html.

For more information, call 1-800-ASK-XEROX or visit us at www.xerox.com/office



² Expected regular monthly throughput

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ Approximate pages. Declared Yield based on 5 page job size, 30% color and 70% Black and white ratio, using letter-/ A4-size media. Yield will vary based on media size, image area coverage, media orientation and usage patterns.